US009408645B2

(12) **United States Patent**
Graca et al.

(10) **Patent No.: US 9,408,645 B2**
(45) **Date of Patent: Aug. 9, 2016**

(54) **INTRAMEDULLARY NAIL LOCKING HOLE ARRANGEMENT**

(75) Inventors: **Claudia Graca**, Kiel (DE); **Annika Homeier**, Kiel (DE); **Ilan Howling**, Kiel (DE); **Edgar Kaiser**, Probsteierhagen (DE)

(73) Assignee: **Stryker European Holdings I, LLC**, Kalamazoo, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1 day.

(21) Appl. No.: **14/343,875**

(22) PCT Filed: **Sep. 16, 2011**

(86) PCT No.: **PCT/EP2011/004657**

§ 371 (c)(1), (2), (4) Date: **Nov. 25, 2014**

(87) PCT Pub. No.: **WO2013/037386**

PCT Pub. Date: **Mar. 21, 2013**

(65) **Prior Publication Data**

US 2015/0080893 A1 Mar. 19, 2015

(51) **Int. Cl.**

A61B 17/72	(2006.01)
A61B 17/17	(2006.01)
A61B 19/00	(2006.01)
A61B 5/06	(2006.01)

(52) **U.S. Cl.**

CPC ***A61B 17/7233*** (2013.01); ***A61B 17/1707*** (2013.01); ***A61B 17/1725*** (2013.01); ***A61B 17/72*** (2013.01); ***A61B 19/54*** (2013.01); *A61B 5/06* (2013.01)

(58) **Field of Classification Search**

USPC 606/62–68

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,475,545	A	10/1984	Ender	
5,041,115	A	8/1991	Frigg et al.	
5,127,913	A *	7/1992	Thomas, Jr.	A61B 17/1707 606/62
5,411,503	A	5/1995	Hollstien et al.	
5,584,838	A	12/1996	Rona et al.	
5,879,352	A	3/1999	Filoso et al.	
6,120,504	A	9/2000	Brumback et al.	
6,270,499	B1	8/2001	Leu et al.	

(Continued)

FOREIGN PATENT DOCUMENTS

CN	100534399	C	9/2009
EP	1382308	A2	1/2004

(Continued)

OTHER PUBLICATIONS

International Search Report and Written Opinion for Application No. PCT/EP2011/004657 dated Jun. 13, 2012.

(Continued)

Primary Examiner — Nicholas Plionis

(74) *Attorney, Agent, or Firm* — Lerner, David, Littenberg, Krumholz & Mentlik, LLP

(57) **ABSTRACT**

An intramedullary nail has a driving end portion and a non-driving end portion with a longitudinal axis. The non-driving end portion comprises a locking hole arrangement with a sequence of four holes, i.e. spaced from non-driving to driving end a first hole, a second hole, a third hole, and a fourth hole. The first hole and the fourth hole have a corresponding first orientation and the second hole and the third hole have a corresponding second orientation.

20 Claims, 3 Drawing Sheets