



US009409447B2

(12) **United States Patent**  
**Takahashi**

(10) **Patent No.:** **US 9,409,447 B2**

(45) **Date of Patent:** **Aug. 9, 2016**

(54) **PNEUMATIC TIRE**

(71) Applicant: **TOYO TIRE & RUBBER CO., LTD.**,  
Osaka-shi, Osaka (JP)

(72) Inventor: **Toshihiko Takahashi**, Osaka (JP)

(73) Assignee: **TOYO TIRE & RUBBER CO., LTD.**,  
Osaka (JP)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 164 days.

(21) Appl. No.: **14/186,346**

(22) Filed: **Feb. 21, 2014**

(65) **Prior Publication Data**

US 2014/0238566 A1 Aug. 28, 2014

(30) **Foreign Application Priority Data**

Feb. 22, 2013 (JP) ..... 2013-033375

(51) **Int. Cl.**

**B60C 11/12** (2006.01)

**B60C 11/117** (2006.01)

**B60C 11/03** (2006.01)

(52) **U.S. Cl.**

CPC ..... **B60C 11/1236** (2013.04); **B60C 11/032** (2013.04); **B60C 11/0304** (2013.04); **B60C 2011/0341** (2013.04); **B60C 2011/0381** (2013.04); **B60C 2011/0388** (2013.04); **B60C 2011/1209** (2013.04)

(58) **Field of Classification Search**

CPC .. B60C 11/03; B60C 11/0304; B60C 11/032; B60C 2011/0341; B60C 2011/0346; B60C 2011/0381; B60C 2011/0383; B60C 2011/0386; B60C 2011/0388; B60C 11/1204; B60C 11/1236; B60C 2011/1245; B60C 2011/1254; B60C 2011/129; B60C 2011/1209; B60C 2011/0374; B60C 2011/0376

USPC ..... 152/209.1, 209.8, 209.17, 209.18

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2009/0272474 A1\* 11/2009 Nagai ..... B60C 11/0318  
152/209.18

2012/0273103 A1\* 11/2012 Ishida ..... B60C 11/0306  
152/209.8

FOREIGN PATENT DOCUMENTS

CN 101360619 A 2/2009  
CN 102756617 A 10/2012

(Continued)

OTHER PUBLICATIONS

JP 2006001357, Jan. 2006, English language machine translation [retrieved from [http://worldwide.espacenet.com/publicationDetails/biblio?DB=worldwide.espacenet.com&II=4&ND=3&adjacent=true&locale=en\\_EP&FT=D&date=20060105&CC=JP&NR=2006001357A&KC=AJ](http://worldwide.espacenet.com/publicationDetails/biblio?DB=worldwide.espacenet.com&II=4&ND=3&adjacent=true&locale=en_EP&FT=D&date=20060105&CC=JP&NR=2006001357A&KC=AJ)].\*

(Continued)

*Primary Examiner* — Eric Hug

(74) *Attorney, Agent, or Firm* — Westerman, Hattori, Daniels & Adrian, LLP

(57) **ABSTRACT**

A pneumatic tire includes a tread having at least one main groove and a plurality of ribs extending in the tire-circumferential direction. At least one of the ribs has a plurality of narrow grooves formed at intervals in the tire-circumferential direction. At least one intermittent sipe is formed corresponding to at least one of the narrow grooves. The narrow grooves are grooves each having a portion extending substantially along the tire-circumferential direction and having a groove width smaller than the at least one main groove. The at least one intermittent sipe has a plurality of holes that are intermittently formed, and at least one solid part located between adjacent two of the holes. The holes and the solid part are arranged in a direction intersecting the narrow grooves. The intermittent sipe intersects the corresponding narrow groove in the at least one solid part.

**4 Claims, 9 Drawing Sheets**

