US007845947B2

(12) **United States Patent**
Rusin et al.

(10) **Patent No.: US 7,845,947 B2**
(45) **Date of Patent: Dec. 7, 2010**

(54) **DENTAL MILL BLANKS**

(75) Inventors: **Richard P. Rusin**, Woodbury, MN (US); **Kevin M. Cummings**, Little Canada, MN (US); **Roger J. Carufel**, Marine on St. Croix, MN (US)

(73) Assignee: **3M Innovative Properties Company**, St. Paul, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 290 days.

(21) Appl. No.: **11/834,999**

(22) Filed: **Aug. 7, 2007**

(65) **Prior Publication Data**

US 2007/0269768 A1 Nov. 22, 2007

Related U.S. Application Data

(60) Continuation of application No. 10/027,278, filed on Dec. 21, 2001, now Pat. No. 7,255,562, which is a division of application No. 09/227,230, filed on Jan. 8, 1999, now abandoned.

(51) **Int. Cl.**
A61K 6/08 (2006.01)

(52) **U.S. Cl.** **433/223**; 264/19

(58) **Field of Classification Search** 433/212.1, 433/213, 223; 264/19
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,066,112	A	11/1962	Bowen
3,117,099	A	1/1964	Proops et al.
3,179,623	A	4/1965	Bowen
3,194,784	A	7/1965	Bowen
3,200,142	A	8/1965	Bowen
3,729,313	A	4/1973	Smith
3,741,769	A	6/1973	Smith
3,751,399	A	8/1973	Lee, Jr. et al.
3,814,717	A	6/1974	Wilson et al.
3,815,239	A	6/1974	Lee, Jr. et al.
3,864,426	A	2/1975	Salensky
3,926,906	A	12/1975	Lee, II et al.
4,129,946	A	12/1978	Kennedy
4,250,053	A	2/1981	Smith
4,297,266	A	10/1981	Ibsen et al.
4,302,381	A	11/1981	Omura et al.
4,394,403	A	7/1983	Smith
4,411,626	A	10/1983	Becker et al.
4,457,714	A	7/1984	Klein
4,479,782	A	10/1984	Orlowski et al.

(Continued)

FOREIGN PATENT DOCUMENTS

DE 282615 A5 9/1990

(Continued)

OTHER PUBLICATIONS

Chemistry and Technology of Epoxy Resins, ed. B. Ellis, Chapman & Hall, Title page, Publication page, and Table of Contents (1993) (7 pgs).

(Continued)

Primary Examiner—Ralph A Lewis

(57) **ABSTRACT**

A dental mill blank comprising a resin, and a filler, wherein the blank is fabricated such that it passes a Thermal Shock Test. The mill blank is substantially free of cracks and discontinuities. Further, the blank may have superior cuttability and hardness.

29 Claims, 1 Drawing Sheet