US009918848B2

(12) **United States Patent**
Waugh et al.

(10) **Patent No.: US 9,918,848 B2**
(45) **Date of Patent: Mar. 20, 2018**

(54) **SPINAL IMPLANT SYSTEM AND METHOD**

(71) Applicant: **Warsaw Orthopedic, Inc.**, Warsaw, IN (US)

(72) Inventors: **Lindsey G. Waugh**, Memphis, TN (US); **Anthony J. Melkent**, Germantown, TN (US); **Jonathan E. Blackwell**, Arlington, TN (US); **Thomas E. Drochner**, Memphis, TN (US); **Carrie L. Gowan**, Memphis, TN (US); **Bret Matthew Wilfong**, Hernando, MS (US); **Thomas A. Carls**, Memphis, TN (US); **Richard A. Hynes**, Melbourne, FL (US); **D. Hal Silcox, III**, Atlanta, GA (US); **John A. Cowan, Jr.**, Rome, GA (US); **Jean-Pierre Mobasser**, Indianapolis, IN (US)

(73) Assignee: **Warsaw Orthopedic, Inc.**, Warsaw, IN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/494,381**

(22) Filed: **Sep. 23, 2014**

(65) **Prior Publication Data**

US 2015/0100129 A1 Apr. 9, 2015

Related U.S. Application Data

(60) Provisional application No. 61/887,794, filed on Oct. 7, 2013.

(51) **Int. Cl.**
A61F 2/44 (2006.01)
A61B 17/70 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC ***A61F 2/442*** (2013.01); ***A61B 17/0206*** (2013.01); ***A61B 17/7059*** (2013.01); ***A61B 17/8042*** (2013.01); ***A61F 2/447*** (2013.01); ***A61F 2/4455*** (2013.01); ***A61F 2/4465*** (2013.01); ***A61F 2/4611*** (2013.01); ***A61F 2/4684*** (2013.01); *A61B 2017/00004* (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61F 2/4611
USPC 623/17.16
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,479,160 B2 * 1/2009 Branch A61B 17/1671 623/17.11
8,268,000 B2 * 9/2012 Waugh A61F 2/4465 623/17.16
(Continued)

FOREIGN PATENT DOCUMENTS

WO 2012103254 A2 8/2002

Primary Examiner — Ellen C Hammond
Assistant Examiner — Stuart S Bray

(57) **ABSTRACT**

A spinal implant comprises an implant body extending between an anterior surface and a posterior surface and includes a first vertebral engaging surface and a second vertebral engaging surface. The implant body includes an inner surface that defines at least one cavity that is oriented to implant a fastener oblique relative to a lateral axis of a subject body and adjacent an intervertebral space of the subject body. The implant body includes an oblique surface that defines at least one opening disposed in substantial alignment with the at least one cavity. Systems and methods are disclosed.

20 Claims, 20 Drawing Sheets