



US005234750A

United States Patent [19]

[11] Patent Number: **5,234,750**

Akao

[45] Date of Patent: **Aug. 10, 1993**

[54] **PACKAGING MATERIAL FOR PHOTSENSITIVE MATERIALS**

[58] Field of Search 524/110, 413, 431; 428/219, 412, 474.4, 475.2, 512, 483, 513, 514, 516, 518, 910

[75] Inventor: **Mutsuo Akao, Kanagawa, Japan**

[56] **References Cited**

[73] Assignee: **Fuji Photo Film Co., Ltd., Minami-Ashigara, Japan**

U.S. PATENT DOCUMENTS

[21] Appl. No.: **856,480**

4,211,852 7/1980 Matsuda et al. 428/521
4,820,757 4/1989 Spang et al. 524/93

[22] Filed: **Mar. 24, 1992**

Primary Examiner—P. C. Sluby
Attorney, Agent, or Firm—Burns, Doane, Swecker & Mathis

Related U.S. Application Data

[62] Division of Ser. No. 483,826, Feb. 23, 1990, abandoned.

[57] **ABSTRACT**

Foreign Application Priority Data

Apr. 20, 1989 [JP] Japan 1-101009
Apr. 20, 1989 [JP] Japan 1-101010
Feb. 23, 1990 [JP] Japan 1-41769

A resin composition containing a light-shielding material and vitamin E and packaging materials formed thereof. The light-shielding ability is increased by blending vitamin E. Laminated films where at least one thermoplastic resin film is interposed between two high Young's modulus films. The laminated films are excellent in tear strength, tensile strength, heat seal strength and bursting strength, and always secure light-shielding, moistureproofness and gas barrier. They can be used as a single-sheet bag for packaging a heavy product having sharp edges.

[51] Int. Cl.⁵ **B32B 27/36; B32B 23/08; B65D 81/30**

[52] U.S. Cl. **428/219; 428/412; 428/474.4; 428/475.2; 428/512; 428/514; 428/516; 428/518; 428/483; 428/910; 428/408; 428/34.3; 264/176.1; 430/501; 426/127**

9 Claims, 4 Drawing Sheets

