US009636950B2

(12) **United States Patent**
Domingo et al.

(10) **Patent No.: US 9,636,950 B2**
(45) **Date of Patent: May 2, 2017**

(54) **TIRE COMPRISING A LAYER OF CIRCUMFERENTIAL REINFORCING ELEMENTS**

(71) Applicants: **Compagnie Generale Des Etablissements Michelin**, Clermont-Ferrand (FR); **Michelin Recherche Et Technique S.A.**, Granges-Paccot (CH)

(72) Inventors: **Alain Domingo**, Clermont-Ferrand (FR); **Jacques Besson**, Clermont-Ferrand (FR); **Francois Barbarin**, Clermont-Ferrand (FR); **Gilles Sallaz**, Clermont-Ferrand (FR); **Robert Ciprian Radulescu**, Clermont-Ferrand (FR)

(73) Assignees: **COMPAGNIE GENERALE DES ETABLISSEMENTS MICHELIN** (FR); **MICHELIN RECHERCHE ET TECHNIQUE S.A.** (CH)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 281 days.

(21) Appl. No.: **14/351,005**

(22) PCT Filed: **Oct. 12, 2012**

(86) PCT No.: **PCT/EP2012/070237**
§ 371 (c)(1),
(2) Date: **Apr. 10, 2014**

(87) PCT Pub. No.: **WO2013/053877**
PCT Pub. Date: **Apr. 18, 2013**

(65) **Prior Publication Data**

US 2014/0283969 A1 Sep. 25, 2014

(30) **Foreign Application Priority Data**

Oct. 13, 2011 (FR) 11 59241

(51) **Int. Cl.**
B60C 9/18 (2006.01)
B60C 9/22 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC ***B60C 9/28*** (2013.01); ***B60C 1/00*** (2013.01); ***B60C 9/18*** (2013.01); ***B60C 9/2006*** (2013.04);
(Continued)

(58) **Field of Classification Search**
CPC B60C 9/18; B60C 9/1835; B60C 9/185; B60C 9/22; B60C 9/28
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,166,267 A * 11/1992 Cohn C08J 3/005 525/173
5,738,740 A * 4/1998 Cluzel B60C 9/1821 152/454
(Continued)

FOREIGN PATENT DOCUMENTS

EP 0722977 A1 7/1996
EP 0849099 A2 6/1998
(Continued)

OTHER PUBLICATIONS

PCT/EP2012/070237, filed Oct. 12, 2012, International Search Report (ISR), Form PCT/ISA/210, dated Jan. 30, 2013 (including English translation), 7 pgs.

Primary Examiner — Justin Fischer
(74) *Attorney, Agent, or Firm* — Dickinson Wright PLLC

(57) **ABSTRACT**

A tire having a crown reinforcement formed of at least two working crown layers having unequal axial widths, a layer C of rubber mixture being positioned between at least the ends of the said at least two working crown layers, and the
(Continued)