US005482551A

United States Patent [19]

Morris et al.

[11] **Patent Number: 5,482,551**

[45] **Date of Patent: Jan. 9, 1996**

[54] **EXTRUDED FIRE RESISTANT CONSTRUCTION AND BUILDING PRODUCTS**

[75] Inventors: **Debra L. Morris**, Oxford; **Albert G. Landers**, Millersville, both of Pa.

[73] Assignee: **Armstrong World Industries, Inc.**, Lancaster, Pa.

[21] Appl. No.: **319,195**

[22] Filed: **Oct. 6, 1994**

Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 123,107, Sep. 20, 1993, abandoned.

[51] **Int. Cl.**[6] **C04B 11/00**

[52] **U.S. Cl.** **106/772**; 106/773; 106/774; 106/778; 106/780; 52/309.12

[58] **Field of Search** 106/772, 774, 106/778, 780, 785, 773; 52/309.12, 309.17, 813, 309.13; 264/176.1, 177.2

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,746,680	7/1973	Boricheski	260/29.2
4,287,103	9/1981	Francis et al.	260/17
4,443,261	4/1984	Nordqvist	106/772
4,686,253	8/1987	Struss et al.	106/675
5,049,196	9/1991	Ries	106/672
5,174,818	12/1992	Symons	106/686
5,277,712	1/1994	McInnis	106/780
5,344,490	9/1994	Roosen et al.	106/778

FOREIGN PATENT DOCUMENTS

614714	2/1961	Canada .
929325	7/1973	Canada .
0056464	3/1984	Japan .
0171261	9/1985	Japan .
881045	11/1981	U.S.S.R. .
984647	3/1965	United Kingdom .
1049184	11/1966	United Kingdom .

Primary Examiner—Paul Marcantoni

[57] **ABSTRACT**

An extrudable composition is provided which is made up primarily of gypsum, a binder/rheology aid and water with a crumbly, semi-dry consistency. The extrudable composition described can be extruded through a die to provide a building product. Density can be minimized and strength optimized by using features of the composition and of the process.

12 Claims, No Drawings