



US006700553B2

(12) **United States Patent**
Becker et al.

(10) **Patent No.:** **US 6,700,553 B2**
(45) **Date of Patent:** ***Mar. 2, 2004**

(54) **BRAILLE COMPUTER MONITOR**

(76) Inventors: **John V. Becker**, deceased, late of New York, NY (US); by David A. Becker, legal representative, 87 Remsen St., Brooklyn, NY (US) 11201; **Daniel E. Hinton**, 815 Galway Garth, Arnold, MD (US) 21012-1342; **Hugh G. Anderson, Jr.**, 1755 Manchester Rd., Westminster, MD (US) 21157

3,510,967 A 5/1970 King et al.
3,594,787 A 7/1971 Ickes
3,659,354 A 5/1972 Sutherland
3,987,438 A 10/1976 Lindenmueller et al.
4,191,945 A * 3/1980 Hannen et al. 340/407.1
4,266,936 A * 5/1981 Rose et al. 434/114
4,445,871 A 5/1984 Becker
4,586,904 A 5/1986 Chlumsky
4,871,992 A 10/1989 Petersen
4,898,536 A * 2/1990 Hoffarth 434/114
5,685,721 A 11/1997 Decker
5,718,588 A 2/1998 Tretiakoff et al.
5,766,014 A 6/1998 Ida et al.
5,767,764 A 6/1998 Ida
5,772,440 A 6/1998 Ida
6,022,220 A 2/2000 Haugen
6,109,922 A * 8/2000 Litschel et al. 434/114
6,417,821 B1 * 7/2002 Becker et al. 345/31

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **10/131,542**

(22) Filed: **Apr. 24, 2002**

(65) **Prior Publication Data**

US 2003/0107531 A1 Jun. 12, 2003

Related U.S. Application Data

(62) Division of application No. 09/605,514, filed on Jun. 28, 2000, now Pat. No. 6,417,821.

(60) Provisional application No. 60/141,329, filed on Jun. 28, 1999.

(51) **Int. Cl.⁷** **G09G 3/00**

(52) **U.S. Cl.** **345/31**; 434/113; 340/407.1

(58) **Field of Search** 345/31, 108; 340/407.1, 340/407.2; 434/112-117

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,363,347 A 1/1968 Benson

* cited by examiner

Primary Examiner—Regina Liang
(74) *Attorney, Agent, or Firm*—Katten Muchin Zavis Rosenman

(57) **ABSTRACT**

A tactual computer monitor includes rows and columns of rectangular cells. Each cell includes four rows and two columns of movable pins which are felt and read by a blind person. The pins are driven by electromechanical impact drivers and are held in position by resilient elastomeric cords. The impact drivers are carried on a bi-directional printhead which travels beneath the movable pins. An erasing mechanism is provided to positively drive the pins downwardly to erase the characters produced by the printhead.

4 Claims, 13 Drawing Sheets

