US009410054B2

(12) **United States Patent**
Coppens et al.

(10) **Patent No.: US 9,410,054 B2**
(45) **Date of Patent: Aug. 9, 2016**

(54) **COMPOSITION AND METHOD FOR PROVIDING STAIN RELEASE OR STAIN REPELLENCY TO SUBSTRATES**

(71) Applicant: **3M INNOVATIVE PROPERTIES COMPANY**, St. Paul, MN (US)

(72) Inventors: **Dirk M. Coppens**, Beveren (BE); **Leonardus A. M. Doelen**, Moenchengladback (DE)

(73) Assignee: **3M Innovative Properties Company**, St. Paul, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 90 days.

(21) Appl. No.: **14/310,688**

(22) Filed: **Jun. 20, 2014**

(65) **Prior Publication Data**

US 2014/0303305 A1 Oct. 9, 2014

Related U.S. Application Data

(62) Division of application No. 13/139,621, filed as application No. PCT/US2009/068018 on Dec. 15, 2009, now abandoned.

(30) **Foreign Application Priority Data**

Dec. 19, 2008 (GB) 0823092.2

(51) **Int. Cl.**

C09D 133/08	(2006.01)
C04B 41/00	(2006.01)
C04B 41/50	(2006.01)
C09D 133/00	(2006.01)
C09D 5/16	(2006.01)

(52) **U.S. Cl.**

CPC ***C09D 133/08*** (2013.01); ***C04B 41/009*** (2013.01); ***C04B 41/5089*** (2013.01); ***C09D 5/1637*** (2013.01); ***C09D 5/1668*** (2013.01); ***C09D 133/00*** (2013.01)

(58) **Field of Classification Search**

CPC C04B 41/009; C04B 41/5089; C04B 41/483; C04B 41/4842

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,395,658	A	3/1995	Jaklin	
5,702,509	A	12/1997	Pellerite	
5,798,415	A	8/1998	Corpart	
7,049,379	B2	5/2006	Jariwala	
7,078,456	B2	7/2006	Jariwala	
7,232,479	B2	6/2007	Poulet	
2002/0045010	A1	4/2002	Rohrbaugh	
2005/0075471	A1	4/2005	Fan	
2005/0288413	A1	12/2005	Zheng	
2007/0066780	A1	3/2007	Ueda	
2007/0167551	A1 *	7/2007	Goodwin	C08K 3/0033 524/442
2007/0197717	A1 *	8/2007	Ueda	C04B 41/009 524/544
2007/0219331	A1	9/2007	Ishikawa	
2008/0113200	A1	5/2008	Peng	
2008/0166486	A1	7/2008	Carcelli	
2011/0086971	A1	4/2011	Ueda	

FOREIGN PATENT DOCUMENTS

CN	1187425	2/2005
CN	101139500	3/2008
EP	1640387	3/2006
EP	1265827	7/2006
EP	1743910	1/2007
JP	11077677	3/1999
JP	11217540	8/1999
JP	2007-070551	3/2007
WO	WO 02-04383	1/2002
WO	WO 2005-083014	9/2005
WO	WO 2007-127267	11/2007
WO	WO 2008/057353	5/2008

OTHER PUBLICATIONS

AATCC—American Association of Textile Chemists and Colorists Test Method 118-1983, "Oil Repellency: Hydrocarbon Resistance Test", 1983, 1page.

International Search Report for PCT/US2009/068018, mailed Aug. 2, 2010, 6 page.

Supplementary European Search Report for EP Application No. 09837876.3, mailed Jun. 8, 2015.

* cited by examiner

Primary Examiner — Wenwen Cai

(57) **ABSTRACT**

The present invention provides a composition for treatment, the composition comprising dispersed in water (i) a fluorinated compound, (ii) a potassium or lithium silicate and (iii) an acrylic polymer. The invention further provides a method of treating substrates with the composition.

17 Claims, No Drawings