



US009410754B2

(12) **United States Patent**  
**Gentilini et al.**

(10) **Patent No.:** **US 9,410,754 B2**  
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **ARM WITH TILTING BARREL GROUP**

(71) Applicant: **FABBRICA D'ARMI PIETRO BERETTA S.p.A.**, Gardone Val Trompia, Brescia (IT)

(72) Inventors: **Claudio Gentilini**, Brescia (IT);  
**Massimiliano Longa**, Brescia (IT)

(73) Assignee: **FABBRICA D'ARMI PIETRO BERETTA S.p.A.**, Brescia (IT)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/114,385**

(22) PCT Filed: **Nov. 23, 2012**

(86) PCT No.: **PCT/IB2012/056683**

§ 371 (c)(1),

(2) Date: **Oct. 28, 2013**

(87) PCT Pub. No.: **WO2013/128248**

PCT Pub. Date: **Sep. 6, 2013**

(65) **Prior Publication Data**

US 2015/0020424 A1 Jan. 22, 2015

(30) **Foreign Application Priority Data**

Feb. 29, 2012 (IT) ..... BS2012A0029

(51) **Int. Cl.**

**F41A 3/60** (2006.01)

**F41A 3/58** (2006.01)

**F41C 7/11** (2006.01)

(52) **U.S. Cl.**

CPC ... **F41A 3/58** (2013.01); **F41A 3/60** (2013.01);

**F41C 7/11** (2013.01)

(58) **Field of Classification Search**

CPC ..... F41A 3/58; F41A 3/60; F41C 7/11

USPC ..... 42/4, 45, 75.044, 75.04, 44

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

93,149 A *	7/1869	Whitney	42/46
161,559 A *	3/1875	Scott	42/44
248,249 A *	10/1881	Baker	42/44
395,849 A *	1/1889	Parry	42/44
399,214 A *	3/1889	Smith	42/41
3,636,646 A	1/1972	Drevet	

FOREIGN PATENT DOCUMENTS

FR	2934363 A3	1/2010
WO	2006/046094 A1	5/2006

\* cited by examiner

*Primary Examiner* — Reginald Tillman, Jr.

(74) *Attorney, Agent, or Firm* — Meunier Carlin & Curfman LLC

(57) **ABSTRACT**

An arm (1) comprises a main body (5), a tilting barrel group (2) fitted to the main body (5) and a locking device (10). The locking device (10) is acting between the main body (5) and the barrel group (2) and manually operable between a locked position, in which the tilting of the barrel group (2) is prevented, and a release position, in which the barrel group (2) is released from said body (5). Said locking device (10) comprises at least one sliding bolt (20) or plug, partially housed in the main body (5) so that, in the locked position, a portion thereof engages the barrel group (2). The device is further comprising a safety catch element (100), acting between the barrel group (2) and the main body (5), which acts in conjunction with the bolt (20) to maintain the locked position.

**10 Claims, 11 Drawing Sheets**

