



US009510655B2

(12) **United States Patent**  
**Stratton**

(10) **Patent No.:** **US 9,510,655 B2**  
(45) **Date of Patent:** **Dec. 6, 2016**

(54) **REMOVABLE MAGNETIC LANYARD FOR HOLDING OR HANGING AN ELECTRONIC DEVICE**

(58) **Field of Classification Search**  
CPC . A45C 13/1069; A45C 13/1076; A45C 13/30; A45C 2011/001; A45F 2005/006; A45F 2200/0508; A45F 2200/0516  
See application file for complete search history.

(71) Applicant: **Daniel John Stratton**, Grapevine, TX (US)

(56) **References Cited**

(72) Inventor: **Daniel John Stratton**, Grapevine, TX (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **Daniel John Stratton**, Grapevine, TX (US)

3,741,376	A	6/1973	Brown et al.	
8,328,055	B1 *	12/2012	Snyder	A45F 5/00 224/197
8,899,458	B1 *	12/2014	Heien	A45F 5/021 224/236
2003/0188815	A1 *	10/2003	Hart	150/147
2007/0215663	A1 *	9/2007	Chongson et al.	224/930
2010/0032462	A1 *	2/2010	Cameron et al.	224/222
2011/0280499	A1 *	11/2011	Brundage	383/11
2016/0003269	A1 *	1/2016	Russell-Clarke	A41F 1/002 24/303

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/612,497**

\* cited by examiner

(22) Filed: **Feb. 3, 2015**

*Primary Examiner* — Thien M Le  
*Assistant Examiner* — Asifa Habib

(65) **Prior Publication Data**

US 2015/0216276 A1 Aug. 6, 2015

(74) *Attorney, Agent, or Firm* — McGinn IP Law Group, PLLC

**Related U.S. Application Data**

(60) Provisional application No. 61/935,231, filed on Feb. 3, 2014.

(57) **ABSTRACT**

(51) **Int. Cl.**  
**G06K 7/00** (2006.01)  
**A45C 11/00** (2006.01)  
**A45F 5/02** (2006.01)  
**A45C 13/10** (2006.01)  
**H01F 7/02** (2006.01)

A device for securing and protecting an item, including a strap comprising a flexible material including a first magnet disposed at a distal end of the strap, and a second magnet disposed at a proximal end of the strap, a casing for securing and protecting the item including a pouch formed in the case having an opening, a screen disposed on a front side of the casing for viewing the item inside the casing, and a border disposed between an edge of the mesh pocket and the screen that surrounds an entirety of the screen, and a connecting region disposed between the distal end of the strap and the casing for securing the strap to the casing.

(52) **U.S. Cl.**  
CPC ..... **A45C 11/00** (2013.01); **A45C 13/1069** (2013.01); **A45F 5/02** (2013.01); **A45F 5/021** (2013.01); **H01F 7/0263** (2013.01); **A45C 2011/002** (2013.01); **A45F 2200/0516** (2013.01)

**12 Claims, 7 Drawing Sheets**

