

11

bimorph actuators to hold the Braille pins in place. This improves manufacturability and serviceability. This low cost part of the design (frame top wall, cell cap, and pins) eliminates the requirement to clean bio-contaminates on a regular basis, as it can now be considered a disposable item. The Braille cell PCB that contains the expensive high voltage control circuitry, expensive bimorph actuators, and critical alignment is reused in a new, clean mechanical chassis/backplane during cleaning or refurbishment of the display.

Frame (chassis/backplane) bottom wall 46 is more fully depicted in FIG. 10. Six (6) threaded inserts, collectively denoted 100, are employed to attach the double decade assembly to the final OEM product. Frame bottom wall 46 is preferably constructed of a material that does not require additional isolation from the metal chassis to which it is mounted. Slots 102 cooperate with slots 72 formed in frame top wall 44 to hold PCBs 36.

FIG. 11 illustrates a set of buttons and a frame 110 for holding the buttons. Each button has a head 112 that is enlarged with respect to its stem 114. Frame 110 has a comb-like construction where the contiguous teeth of the comb are spaced apart from one another by a space that slideably receives a stem 114. The teeth of the comb thus support heads 112. Buttons 110 perform functions relating to cursor location and panning features.

FIG. 12 depicts the novel double decade Braille cell assembly without the novel cell cap. Note that there are two (2) button and frame assemblies 110 of the type depicted in FIG. 11 and that said assemblies 110 are disposed in confronting relation to one another.

FIG. 13 depicts the double decade Braille cell assembly with the novel cell cap 92 in its functional position. All pins are in their retracted position in this Fig.

The modularization provided by the novel design is a key to success in providing a low cost product that is economical to manufacture and easy to service. Each of the Braille cells can be individually installed or removed from service as a result of the backplane/chassis solution. The backplane/chassis provides the benefits of electrical interconnect, correct mechanical alignment, high voltage isolation, and a stable platform for additional circuitry such as tactile switches commonly used for routing the cursor to a specified cell location.

Any number of cells may be used in the modularization, and each module is interconnectable to another module. For commercial purposes, the minimum-sized module has been selected at twenty (20) cells, thereby enabling the selling of products including twenty (20) cells, forty (40) cells, sixty (60) cells, eighty (80) cells, and so on. Other module sizes are within the scope of this invention. For example, production of a four (4) cell module would enable production of a forty four (44) cell Braille display (20+20+4), a seventy-two cell Braille display (20+20+20+4+4+4), an eighty four (84) cell Braille display (20+20+20+20+4), and so on.

The provision of the monolithic cell cap also produces an array of button caps over the tact switches. This array of button caps reduces labor costs. Prior art Braille dell manufacturers require each switch cap be individually installed.

12

It will be seen that the advantages set forth above, and those made apparent from the foregoing description, are efficiently attained and since certain changes may be made in the above construction without departing from the scope of the invention, it is intended that all matters contained in the foregoing description or shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense.

It is also to be understood that the following claims are intended to cover all of the generic and specific features of the invention herein described, and all statements of the scope of the invention that, as a matter of language, might be said to fall therebetween. Now that the invention has been described,

What is claimed is:

1. A Braille cell assembly, comprising:

a monolithic Braille cell cap that encases a plurality of Braille cells;

said monolithic cap enhancing the tactile feel of a Braille cell assembly by eliminating the uneven surface provided by a plurality of individual Braille cell caps, said monolithic Braille cell cap comprising a top plate and a plurality of side walls such that the side walls are approximately perpendicularly connected to the top plate;

a first plurality of buttons;

a first frame interconnected to each of the first plurality of buttons;

each button of said first plurality of buttons having a head and a stem;

the individual buttons being resiliently retained by the first frame, whereby the head of each button can be independently depressed.

2. The Braille cell assembly of claim 1, further comprising: a second plurality of buttons;

a second frame for holding the second plurality of buttons; each button of said second plurality of buttons having a head and a stem, said head being enlarged with respect to its stem;

said second frame including contiguous teeth that are spaced apart from one another;

and each button being mounted to a free end of each tooth.

3. The Braille cell assembly of claim 2, further comprising: said first and second frames being mounted to a top wall of a Braille cell assembly frame in confronting relation to one another.

4. The Braille cell assembly of claim 3, further comprising: said monolithic cap covering said first and second frames; said monolithic cap being releasably engaged to said top wall of said frame.

5. The Braille cell assembly of claim 1, further comprising: at least one protuberance approximately perpendicularly connected to at least one side wall, such that the at least one protuberance is approximately parallel to the top plate of the monolithic cell cap, the at least one protuberance further comprising a means for connecting the monolithic cell cap to a top wall of a Braille cell assembly frame.

* * * * *