US007406057B2

(12) **United States Patent**
Isomäki et al.

(10) **Patent No.: US 7,406,057 B2**
(45) **Date of Patent: Jul. 29, 2008**

(54) **METHOD FOR HANDLING OF MESSAGES BETWEEN A TERMINAL AND A DATA NETWORK**

(75) Inventors: **Markus Isomäki**, Espoo (FI); **Tuija Hurtta**, Espoo (FI); **Serge Haumont**, Helsinki (FI)

(73) Assignee: **Spyder Navigations L.L.C.**, Wilmington, DE (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 897 days.

(21) Appl. No.: **10/493,809**

(22) PCT Filed: **Oct. 31, 2001**

(86) PCT No.: **PCT/EP01/12630**

§ 371 (c)(1),
(2), (4) Date: **Apr. 27, 2004**

(87) PCT Pub. No.: **WO03/039080**

PCT Pub. Date: **May 8, 2003**

(65) **Prior Publication Data**

US 2004/0259532 A1 Dec. 23, 2004

(51) **Int. Cl.**
H04Q 7/00 (2006.01)

(52) **U.S. Cl.** **370/328**; 370/338; 370/401

(58) **Field of Classification Search** ..... None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,707,813 B1 * 3/2004 Hasan et al. 370/356
7,065,339 B2 * 6/2006 Vallinen et al. 455/406
7,116,967 B2 * 10/2006 Kauppinen et al. 455/404.1
7,120,156 B2 * 10/2006 Foti et al. 370/401
2002/0064164 A1 * 5/2002 Barany et al. 370/401
2002/0126701 A1 * 9/2002 Requena 370/469
2002/0147824 A1 * 10/2002 Hurtta et al. 709/230
2003/0086410 A1 * 5/2003 Eikkula 370/352

FOREIGN PATENT DOCUMENTS

WO WO 99/48310 9/1999
WO WO 00/70825 11/2000

OTHER PUBLICATIONS

3GPP TS 23.107 V3.4.0, Technical specification, "3rd Generation Partnership Project; Technical Specificatoin Group Services and System Aspects; QoS Concept and Architecture (Release 1999)"; pp. 1-36.

Puuskari Mikko "Quality of Service Framework in GPRS and Evolution Towards UMTS"; 3rd European Personal Mobile Communication Conference, Paris, Mar. 9-11, 1999; 7 sheets.

* cited by examiner

Primary Examiner—Bob A Phunkulh

(57) **ABSTRACT**

A method for handling of messages between a terminal and a data network, in which messages of a specific protocol are handled using correspondingly defined specific contexts for messages of the protocol. Messages based on the same specific protocol relate to different service categories. A message is received at the network, and an analysis of the message is performed to determine a service category of the received message. A different specific context is assigned to each received message dependent on the analyzed service category.

20 Claims, 4 Drawing Sheets