

- [54] **SAMPLING CATHETER DEVICE**
- [75] Inventor: **John Anthony Gaskell, Box Hill, Australia**
- [73] Assignee: **Smith & Nephew (Australia) Pty. Limited, Australia**
- [22] Filed: **Jan. 22, 1976**
- [21] Appl. No.: **651,226**
- [30] **Foreign Application Priority Data**
 Jan. 28, 1975 Australia 0376/75
- [52] **U.S. Cl.** **128/2 W; 128/2B; 128/269; 128/348**
- [51] **Int. Cl.²** **A61M 25/00; A61B 10/00**
- [58] **Field of Search** **128/240-241, 128/348-351, 345, 2 R, 2 B, 2 W, 269, 304**
- [56] **References Cited**
UNITED STATES PATENTS
 217,711 7/1879 Shiland 128/349 R

1,595,180	8/1926	Fisher	128/240
3,037,496	6/1962	Melges	128/2 W
3,513,830	5/1970	Kalayjian	128/2 W
3,776,219	12/1973	Brown	128/2 B

Primary Examiner—Dalton L. Truluck
Attorney, Agent, or Firm—Buell, Blanko & Ziesenheim

[57] **ABSTRACT**

A sampling catheter comprises an outer tube of resilient material which has an open and a closed end. The closed end is shaped so as to permit unrestricted entry into a body through a channel thereof and has means associated therewith enabling the opening of the closed end and protrusion therethrough by an inner tube extending within the outer tube upon said inner tube being pushed against the closed end.

A sampling sway is provided within the inner tube for extension beyond the end of the inner tube after protrusion thereof through the closed end.

3 Claims, 2 Drawing Figures

