



US009410360B2

(12) **United States Patent**
Wei

(10) **Patent No.:** **US 9,410,360 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **DOOR ASSEMBLY**

E05Y 2600/522 (2013.01); *E05Y 2600/56*
(2013.01); *E05Y 2600/62* (2013.01); *E05Y*
2900/132 (2013.01)

(71) Applicant: **Foshan Ideal Co., Ltd.**, Foshan,
Guangdong (CN)

(72) Inventor: **Wuxiang Wei**, Foshan (CN)

(73) Assignee: **Foshan Ideal Co., Ltd.**, Gaoming,
Foshan Guangdong (CN)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/918,552**

(22) Filed: **Jun. 14, 2013**

(65) **Prior Publication Data**

US 2014/0331565 A1 Nov. 13, 2014

(30) **Foreign Application Priority Data**

May 13, 2013 (CN) 2013 2 0256871 U

(51) **Int. Cl.**

- E06B 3/964** (2006.01)
- E05D 11/00** (2006.01)
- E05D 7/081** (2006.01)
- A47K 3/36** (2006.01)
- E06B 5/00** (2006.01)
- A47K 3/30** (2006.01)

(52) **U.S. Cl.**

CPC . **E06B 3/964** (2013.01); **A47K 3/36** (2013.01);
E05D 7/081 (2013.01); **E05D 11/0054**
(2013.01); **E06B 5/00** (2013.01); **A47K**
2003/307 (2013.01); **E05Y 2201/11** (2013.01);
E05Y 2600/12 (2013.01); **E05Y 2600/14**
(2013.01); **E05Y 2600/312** (2013.01); **E05Y**
2600/324 (2013.01); **E05Y 2600/502** (2013.01);

(58) **Field of Classification Search**

CPC E06B 1/045; E06B 1/603; E06B 1/6069
USPC 49/504, 505, 55, 176, 177, 396; 4/607,
4/557; 52/126.1, 126.3, 127.7, 656.9
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 3,226,897 A * 1/1966 Dorman 52/781
- 4,251,962 A * 2/1981 Langenhorst 52/127.7
- 4,646,472 A * 3/1987 Sugawara 49/386
- 4,720,876 A * 1/1988 Tomei et al. 4/614
- 4,914,770 A * 4/1990 Baus 4/612
- 4,958,462 A * 9/1990 Cross 49/181

(Continued)

FOREIGN PATENT DOCUMENTS

GB 2 440 605 A 2/2008

Primary Examiner — Gregory Strimbu

(74) *Attorney, Agent, or Firm* — Sheppard Mullin Richter &
Hampton LLP

(57) **ABSTRACT**

A door assembly comprises a stationary frame, a movable
frame, and an adjusting assembly. The adjusting assembly
comprises an adjusting element detachably connected with
the stationary frame and having a rod portion; a fixing ele-
ment connected with the movable frame and having a cavity
for receiving the rod portion; and a cam member disposed
adjacent to the cavity and movable between an open position
in which the movable frame is movable relative to the station-
ary frame and a closed position in which the movable frame is
fixed relative to the stationary frame. The door assembly can
be assembled without drilling, minimizing risk of damage to
the frames, and can be assembled by a single person.

8 Claims, 6 Drawing Sheets

