



US009410364B1

(12) **United States Patent**  
**Zheng**

(10) **Patent No.:** **US 9,410,364 B1**  
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **SEALED MAGNETIC-CONTROLLED WINDOW BLIND BETWEEN TWO PANES OF GLASS**

- (71) Applicant: **Supreme Plastic Products Co., Ltd.**, Guangdong (CN)
- (72) Inventor: **Song-Li Zheng**, Guangdong (CN)
- (73) Assignee: **Supreme Plastic Products Co., Ltd.**, Qingyuan, Guangdong (CN)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/859,212**  
(22) Filed: **Sep. 18, 2015**

- (51) **Int. Cl.**  
*E06B 9/264* (2006.01)  
*E06B 9/322* (2006.01)  
*E06B 7/12* (2006.01)
- (52) **U.S. Cl.**  
CPC . *E06B 9/264* (2013.01); *E06B 7/12* (2013.01);  
*E06B 9/322* (2013.01); *E06B 2009/2643* (2013.01); *E06B 2009/2646* (2013.01)

(58) **Field of Classification Search**  
CPC ..... *E06B 2009/2646*; *E06B 2009/2643*; *E06B 7/12*  
USPC ..... 160/107, 168.1 R, 176.1 R, 170, 171, 160/DIG. 16  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,601,633 B2 *	8/2003	Sun	.....	E06B 9/264
				160/107
7,000,670 B2 *	2/2006	Kwon	.....	E06B 9/264
				160/107
7,475,715 B2 *	1/2009	Gardner	.....	E06B 9/264
				160/107
7,669,633 B2 *	3/2010	Berger	.....	E06B 9/264
				160/107
8,499,815 B2 *	8/2013	Zhang	.....	E06B 9/264
				160/107
8,550,141 B2 *	10/2013	Ding	.....	E06B 9/264
				160/107
2006/0118250 A1 *	6/2006	Jin	.....	E06B 9/264
				160/107

\* cited by examiner

*Primary Examiner* — David Puroil  
(74) *Attorney, Agent, or Firm* — Yuwen Guo

(57) **ABSTRACT**

A sealed magnetic-controlled window blind between two panes of glass is disclosed. Raising or lowering the window blind which is sealed between two panes of glass is performed by the magnetic attraction between the between the raising outside control set and the raising inside control set (the magnets may be used). In addition, the operation of raising or lowering the window blind may be smooth due to the arrangement of the pulleys (or bearing) which are arranged on the raising inside control set and the outside control set.

**3 Claims, 3 Drawing Sheets**

