



US009410764B2

(12) **United States Patent**
Jarboe

(10) **Patent No.:** **US 9,410,764 B2**
(45) **Date of Patent:** ***Aug. 9, 2016**

- (54) **BUTTSTOCK ASSEMBLY**
- (71) Applicant: **RA BRANDS, L.L.C.**, Madison, NC (US)
- (72) Inventor: **M. Brent Jarboe**, Rineyville, KY (US)
- (73) Assignee: **RA Brands, L.L.C.**, Madison, NC (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

- (21) Appl. No.: **14/466,328**
- (22) Filed: **Aug. 22, 2014**

(65) **Prior Publication Data**
US 2014/0360074 A1 Dec. 11, 2014

Related U.S. Application Data
(62) Division of application No. 13/573,156, filed on Aug. 27, 2012, now Pat. No. 8,844,185.

(51) **Int. Cl.**
F41C 23/14 (2006.01)
F41C 23/04 (2006.01)
F41C 23/06 (2006.01)
F41C 23/08 (2006.01)

(52) **U.S. Cl.**
CPC **F41C 23/14** (2013.01); **F41C 23/04** (2013.01); **F41C 23/06** (2013.01); **F41C 23/08** (2013.01)

(58) **Field of Classification Search**
CPC F41C 23/04; F41C 23/14; F41C 23/06; F41C 23/08; F41C 27/00
USPC 42/71.01, 72-74, 90, 75.01-75.03
See application file for complete search history.

- (56) **References Cited**
U.S. PATENT DOCUMENTS

543,138 A 7/1895 Murray
1,315,215 A 9/1919 Davidson
1,407,633 A 2/1922 Burton

(Continued)

- FOREIGN PATENT DOCUMENTS**

CH 126420 6/1928
DE 1213303 3/1966

(Continued)

- OTHER PUBLICATIONS**

"Zweibein im Vorderschaft verschiebbar"; DWJ Deutsches Waffen Journal; pp. 878-879; vol. 30, No. 6, Jun. 1, 1994.

(Continued)

Primary Examiner — Michael David
(74) *Attorney, Agent, or Firm* — David Sudderth

(57) **ABSTRACT**
A modular firearm comprising an adjustable modular buttstock assembly. The buttstock assembly can include a frame with a central opening. A comb assembly having a cheek piece and a butt plate assembly having a recoil pad each can be mounted to the frame by an adjustment apparatus. Each adjustment apparatus can include of a guide post and/or a threaded adjustment post each received in respective bores in the frame to adjust the positions of the cheek piece and recoil pad. The adjustment apparatus also can include a locking or engagement feature that can selectively increase the friction between the frame and the guide post and/or adjustment post, to help prevent the translation of the guide post and/or adjustment post in the bore in the frame to fix the comb assembly and butt plate assembly in desired positions with respect to the frame.

12 Claims, 12 Drawing Sheets

