



US009410765B2

(12) **United States Patent**  
**Bednar et al.**

(10) **Patent No.:** **US 9,410,765 B2**  
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **CROSSBOW INTEGRATED GRIP GUARD**

(71) Applicants: **Hunter's Manufacturing Company, Inc.**, Suffield, OH (US); **Richard L. Bednar**

(72) Inventors: **Richard L. Bednar**, Munroe Falls, OH (US); **Michael J. Shaffer**, Mogadore, OH (US); **Jacob A. Hout**, Akron, OH (US); **William J. Bednar**, Akron, OH (US)

(73) Assignee: **Hunter's Manufacturing Co., Inc.**, Suffield, OH (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/173,319**

(22) Filed: **Feb. 5, 2014**

(65) **Prior Publication Data**

US 2015/0219420 A1 Aug. 6, 2015

(51) **Int. Cl.**  
**F41B 5/12** (2006.01)  
**F41C 23/16** (2006.01)  
**F41B 5/14** (2006.01)

(52) **U.S. Cl.**  
CPC . **F41C 23/16** (2013.01); **F41B 5/12** (2013.01);  
**F41B 5/1426** (2013.01); **F41B 5/1469**  
(2013.01)

(58) **Field of Classification Search**

CPC ..... F41B 5/12; F41B 5/148; F41C 23/16  
USPC ..... 124/25  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

6,988,495	B1 *	1/2006	Van Hoon	.....	F41B 5/14	124/88
7,455,059	B2	11/2008	Shaffer			
7,661,418	B2	2/2010	Bednar et al.			
8,061,339	B2	11/2011	Shaffer			
8,127,752	B2	3/2012	Bednar et al.			
8,220,445	B2 *	7/2012	Bednar	.....	F41B 5/123	124/25
2012/0006311	A1	1/2012	Bednar et al.			
2012/0266514	A1 *	10/2012	Michal	.....	F41C 23/16	42/90

\* cited by examiner

*Primary Examiner* — Gene Kim

*Assistant Examiner* — Jeffrey Vanderveen

(74) *Attorney, Agent, or Firm* — Emerson Thomson Bennett

(57) **ABSTRACT**

A grip guard may be used with a crossbow that has a main beam including a stock and a barrel. The grip guard may have a first wall that is positioned between the stock and the barrel and a second wall that extends outwardly from the main beam. The first wall may have dampening properties to attenuate sounds and vibrations caused by firing the crossbow and the second wall may prevent a user's fingers from inadvertently extending from the handle toward the barrel.

**15 Claims, 16 Drawing Sheets**

