

# INTRAOCULAR LENS WITH HIGH MAGNIFICATION

## BRIEF DESCRIPTION

This invention relates to an intraocular lens system for implantation in the eye for relief of conditions such as macular degeneration and diabetic retinopathy.

Heretofore, people suffering from macular degeneration or diabetic retinopathy have been unable to read except through strong magnifying glasses which require the reading matter to be held very closely to the eye and provide a very severely restricted field of view.

The invention contemplates an optical system for implantation in the eye that will permit reading at normal distances, say about thirty centimeters, between the eye and the printed page, and provide a much larger field of view than heretofore possible with simple magnifiers.

The system of the invention makes use of gas filled bubbles in solid bodies of transparent plastic to achieve the refraction needed for focussing in the relatively short space available inside the eye. The system is, in optical engineering terms, a Galilean telescope. Its positive element consists of a body of methyl methacrylate having a bubble in it bounded by optically curved front and back surfaces, and may be described as either a biconcave air lens within a solid medium (positive power) or two biconvex plastic lenses in tandem. Because the refractive index of the aqueous humour is relatively close to the index of the acrylic material, and the front and rear surfaces, therefore, provide relatively little refraction, it is believed that the term air lens is more apt.

The negative element of the system is composed of a second cylinder of methyl methacrylate having one or more air lenses to provide the negative power required. The positive and negative elements are mechanically secured to each other, and the positive element is surgically secured in place near the pupil. The exit end of the negative element lies a few millimeters in front of the retina.

The air lenses not only enable the achievement of adequate focussing in the short distance available, but also enable matching the specific gravity of the system to the specific gravity of the aqueous humour so that the system will have neutral buoyancy in the aqueous humour, or the salt solution that may be used to replace it and most of the vitreous humour, and not tend to pivot in response to gravity about its point of attachment near the pupil.

## DETAILED DESCRIPTION

Representative embodiments of the invention will now be described in detail in conjunction with the accompanying drawing, wherein:

FIG. 1 is a longitudinal sectional view of an optical system according to the invention having smoothly curved optical surfaces; and

FIG. 2 is a longitudinal sectional view of an optical system according to a modified form of the invention having optical surfaces of the micro-Fresnel type.

Referring now to FIG. 1, a lens system according to a first embodiment of the invention comprises a first element 14 having an optical power of about 126 diopters, more or less, depending on the dimensions of the eye for which it is intended. Also, if the patient's cornea has been damaged or is opacified, it is contemplated that

the positive element will be extended through the cornea, and its power increased by about 38 to 48 diopters so that it will include the power normally provided by the cornea.

The front and rear surfaces 14a and 14b, respectively, of the element 14 are convex, and the element encloses a bubble 15 having front and rear surfaces 15a and 15b, respectively, that are also convex as seen from each other. The bubble 15, regarded in section, may be designated a biconcave air lens, and it is this air lens that provides most of the positive refractive power of the element because the outer convex surfaces 14a and 14b contact the aqueous humour when the lens is in place, and the refractive indices of the aqueous humour and methyl methacrylate are not very different from each other.

The element 14 is arranged to be secured to an element of the eye such as the iris by any desired means such as clips or simple sutures (not shown). Several different arrangements for securing intraocular lenses near the pupil are known, and the particular method of attachment is not a part of the present invention nor limiting to it.

The negative element 18 is mechanically fastened to the positive element 14 by any desired means that do not obstruct the path of light between the two elements. As shown, the attachment is by three angularly spaced methyl methacrylate pins 17, which may be cemented in receptor holes (not designated) in the respective elements 14 and 18. The two elements 14 and 18, taken together with the connecting means, constitute a body of a size and shape for implantation in the human eye.

A total power of about -2000 diopters is needed in the negative element 18, and to achieve this in the embodiment of FIG. 1, two air lenses 20 and 22, respectively, are arranged in tandem. Again, as with the positive element, the principal refractive surfaces are those facing the air in the bubbles 20 and 22, although in all cases the curvatures of the methacrylate-aqueous humour interfaces should be taken into account.

It will be recognized that with the relatively large number of refractive surfaces in the system, there can be found many different combinations of curvatures for the various surfaces and the spacings between them that will provide the desired overall power. Accordingly, the specific curvatures and spacings given in the following Table are illustrative only. They characterize an optical design based on an entrance pupil of 2 mm. diameter, and optimized in respect of geometrical image quality, taking into account also the curvature of the retina.

### TABLE

Surface	LENS DESIGN	
	Radius of Curvature, mm.	Distance to next rearward surface, mm.
Object (not shown)	plano	300.
Front 12a of cornea	+7.9800	1.1500
Rear 12b of cornea	+6.2200	1.9954
Front 14a of pos. element	+8.9978	1.0000
Front 15a of pos. bubble	-9.0023	0.5004
Rear 15b of pos. bubble	+9.0015	1.0000
Rear 14b of pos. element	-9.0023	3.3946
Front 18a of neg. element	-2.2012	1.0004
Front 20a of 1st bubble	+2.1981	2.0000
Rear 20b of 1st bubble	-2.1915	0.9980
Front 22a of 2nd bubble	+2.2055	2.0000
Rear 22b of 2nd bubble	-2.0488	0.1284
Rear 18b of neg. element	+9.3925	8.8317
Retina 24	-12.0000	