



US009408769B2

(12) **United States Patent**
Koch

(10) **Patent No.:** **US 9,408,769 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **EXTENSION DEVICE**
(75) Inventor: **Guido Koch**, Karlsruhe (DE)
(73) Assignee: **MAQUET GMBH**, Rastatt (DE)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 675 days.

2007/0156122 A1* 7/2007 Cooper 606/1
2007/0265635 A1* 11/2007 Torrie et al. 606/105
2011/0023893 A1* 2/2011 Striggow et al. 128/882

FOREIGN PATENT DOCUMENTS

CN 101700656 A 5/2010
DE 20 2009 013 905 U1 2/2010
JP 2009525767 A 7/2009
WO 2009062324 A1 5/2009

(21) Appl. No.: **13/369,466**
(22) Filed: **Feb. 9, 2012**
(65) **Prior Publication Data**
US 2012/0204885 A1 Aug. 16, 2012

OTHER PUBLICATIONS

European Patent Application Search Report for European Patent Application No. EP12154697.2 dated May 30, 2012.
The English Translation of Office Action and Search Report for Chinese Patent Application No. CN201210028864.5 dated Dec. 17, 2013.
English Translation of a Notification of Provisional Refusal for Japanese Patent Application JP2012024986 dated Apr. 16, 2013.

(30) **Foreign Application Priority Data**
Feb. 10, 2011 (DE) 20 2011 000 308

* cited by examiner

Primary Examiner — Ophelia A Hawthorne

(51) **Int. Cl.**
A61G 13/12 (2006.01)
A61F 5/042 (2006.01)
A61G 13/10 (2006.01)
A61B 17/60 (2006.01)
(52) **U.S. Cl.**
CPC *A61G 13/1245* (2013.01); *A61F 5/042* (2013.01); *A61G 13/101* (2013.01); *A61B 17/60* (2013.01)

(57) **ABSTRACT**

An extension device includes a patient support surface and an extension beam (16) that can be connected via an interface (14) to the patient support surface and that has a holder for a feed rod arrangement. The patient support surface has at least two longitudinal beams (10) parallel to each other that carry a pelvic support plate. The interface (14) includes a coupling part (36) on the support surface side and a coupling part (38) on the beam side rigidly connected to the extension beam (16). The coupling part (36) on the support surface side on one of the longitudinal beams (10) is supported such that it can pivot about an axis perpendicular to the pelvic support plate, and whereby the coupling part (36) on the support surface side can be locked by a locking device, which may be actuated by remote actuation, against a rotation about its pivot axis relative to the longitudinal beam (10).

(58) **Field of Classification Search**
USPC 128/845–846, 882; 5/619–621, 5/623–624; 602/32, 35; 606/54, 57
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS
4,146,793 A * 3/1979 Bergstrom et al. 378/161
4,940,218 A 7/1990 Akcelrod
5,645,079 A 7/1997 Zahiri et al.
2006/0185090 A1 8/2006 Jackson

20 Claims, 5 Drawing Sheets

