



(12) **United States Patent**
Atkins et al.

(10) **Patent No.:** **US 9,410,570 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **CLAMP**

(71) Applicant: **Specialised Petroleum Services Group Limited**, Aberdeen, Aberdeenshire (GB)

(72) Inventors: **James Edward Atkins**, Aberdeen (GB); **George Telfer**, Aberdeen (GB); **Edward Docherty Scott**, Cardenden (GB)

(73) Assignee: **Specialised Petroleum Services Group Limited**, Aberdeen, Aberdeenshire (GB)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 666 days.

(21) Appl. No.: **13/784,261**

(22) Filed: **Mar. 4, 2013**

(65) **Prior Publication Data**

US 2013/0174408 A1 Jul. 11, 2013

Related U.S. Application Data

(62) Division of application No. 11/661,070, filed as application No. PCT/GB2005/003273 on Aug. 23, 2005, now Pat. No. 8,388,256.

(30) **Foreign Application Priority Data**

Aug. 24, 2004 (GB) 0418796.9

(51) **Int. Cl.**

B25G 3/20 (2006.01)
F16B 2/14 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **F16B 37/00** (2013.01); **B23P 11/00** (2013.01); **E21B 37/02** (2013.01); **F16B 2/065** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC Y10T 403/14; Y10T 403/142; Y10T 403/7062; Y10T 403/7067; E21B 37/02; F16B 2/065; F16B 41/005; F16B 37/00

USPC 403/17, 195, 256-263, 289, 292, 309, 403/312, 313, 335-337, 344, 373, 374.4, 403/379.2, 379.3, 408.1, DIG. 12, DIG. 13; 166/242.6; 411/104

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,412,876 A 12/1946 Edwards
2,713,913 A 7/1955 Ragan

(Continued)

FOREIGN PATENT DOCUMENTS

FR 2755492 A1 5/1998
GB 2072296 A 9/1981

(Continued)

OTHER PUBLICATIONS

French Application Registration No. 96 13705 filed on May 11, 1996 entitled "Anti-Fraud System for Fluid Distribution Network" in its entirety, 20 pages.

(Continued)

Primary Examiner — Gregory Binda

Assistant Examiner — Nahid Amiri

(74) *Attorney, Agent, or Firm* — Osha Liang LLP

(57) **ABSTRACT**

A clamp holds two members together. The first member includes a recess into which a fastener is located. A bore is provided to the recess to allow a tool to be used to operate the fastener. The second member is arranged to accept the fastener and so join the members. The recess and bore are sized to prevent release of the fastener through the bore. In this way, the fastener cannot easily be removed or lost when the clamp is in use and is tamperproof. The clamp is used to hold portions of a sleeve around a body of the tool, and to hold scraper blades and/or brushes to the body.

10 Claims, 5 Drawing Sheets

