



US009510970B2

(12) **United States Patent**
Slusarz, Jr.

(10) **Patent No.:** **US 9,510,970 B2**

(45) **Date of Patent:** ***Dec. 6, 2016**

(54) **BOOT WITH LOCKABLE STRAP**

(71) Applicant: **Smith & Nephew, Inc.**, Memphis, TN (US)

(72) Inventor: **John Albert Slusarz, Jr.**, Hopedale, MA (US)

(73) Assignee: **Smith & Nephew, Inc.**, Memphis, TN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/597,594**

(22) Filed: **Jan. 15, 2015**

(65) **Prior Publication Data**

US 2015/0122268 A1 May 7, 2015

Related U.S. Application Data

(63) Continuation of application No. 14/012,238, filed on Aug. 28, 2013, now Pat. No. 8,944,065.

(Continued)

(51) **Int. Cl.**

A61F 5/37 (2006.01)

A61G 13/12 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A61F 5/37** (2013.01); **A61B 5/0555** (2013.01); **A61F 5/0116** (2013.01); **A61F 5/3769** (2013.01); **A61G 13/1245** (2013.01)

(58) **Field of Classification Search**

CPC **A61G 13/00**; **A61G 13/0036**; **A61G 13/10**; **A61G 13/12**; **A61G 13/123**; **A61G 13/1245**; **A61G 13/125**; **A61G 2013/0063**;

A61G 2013/0081; A61F 5/00; A61F 5/0111; A61F 5/0127; A61F 5/37; A61F 5/3761; A61F 5/3769; A43C 7/08; A43C 11/14; A43B 5/04

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,442,266 A 5/1948 Davis
2,665,431 A * 1/1954 Elsner A61G 1/06
24/134 KB

(Continued)

FOREIGN PATENT DOCUMENTS

EP 2529719 A3 7/2013
WO WO2007021806 A3 5/2007
WO WO2009059434 A1 5/2009

OTHER PUBLICATIONS

“Trail Hiking Snowshoes for Women—Silver 9 by Crescent Moon,” reprinted from <http://crescentmoonsnowshoes.com/womens/silver9.php>, accessed Aug. 28, 2013.

(Continued)

Primary Examiner — Ophelia A Hawthorne

Assistant Examiner — Keri J Nelson

(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

In some implementations, a boot includes an outer shell having a first side and a second side located opposite the first side. The boot also includes a retention strap, a first one-way tensioning device, and a second one-way tensioning device. The first one-way tensioning device is coupled to the first side of the outer shell, and the first one-way tensioning device is configured to allow movement of the retention strap in a first direction and to restrain movement of the retention strap opposite the first direction. The second one-way tensioning device is coupled to the second side of the outer shell, and the second one-way tensioning device is configured to allow movement of the retention strap in a

(Continued)

