



(12) **United States Patent**
Kim

(10) **Patent No.:** **US 9,408,472 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **LEG REST DEVICE**

(71) Applicants: **Hyundai Motor Company**, Seoul (KR);
KIA MOTORS CORP., Seoul (KR)

(72) Inventor: **Bong Ku Kim**, Gunpo-si (KR)

(73) Assignees: **Hyundai Motor Company**, Seoul (KR);
KIA MOTORS CORP., Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/535,063**

(22) Filed: **Nov. 6, 2014**

(65) **Prior Publication Data**

US 2016/0000227 A1 Jan. 7, 2016

(30) **Foreign Application Priority Data**

Jul. 4, 2014 (KR) 10-2014-0083913

(51) **Int. Cl.**

A47C 7/50 (2006.01)
B60N 2/44 (2006.01)
B64D 11/06 (2006.01)
B60N 2/02 (2006.01)

(52) **U.S. Cl.**

CPC **A47C 7/506** (2013.01); **B60N 2/4495**
(2013.01); **B64D 11/0643** (2014.12); **B60N**
2002/024 (2013.01)

(58) **Field of Classification Search**

CPC **A47C 1/034**; **A47C 1/0355**; **A47C 7/50**;
A47C 7/506; **B60N 2/4495**; **B60N 3/063**;
B64D 11/0643
USPC **297/69**, **84**, **85 R**, **85 M**, **423.19**, **423.26**,
297/423.28, **423.3**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,871,917 A * 2/1959 Schliephacke A47C 1/0355
297/85 R
3,014,758 A * 12/1961 Schliephacke A47C 1/035
297/89
3,140,893 A * 7/1964 Schliephacke A47C 1/0345
297/85 R
3,794,381 A * 2/1974 Caldemeyer A47C 7/506
297/423.22
5,505,519 A * 4/1996 Natt B60N 2/28
297/250.1
2002/0113476 A1* 8/2002 Enno B64D 11/06
297/330
2013/0313867 A1* 11/2013 Kuno B60N 2/62
297/83
2013/0341989 A1* 12/2013 Lin A47C 7/506
297/423.28
2014/0145476 A1* 5/2014 Nagayasu B60N 2/22
297/86

FOREIGN PATENT DOCUMENTS

GB 813023 A * 5/1959 A47C 1/0355
JP H11-332688 A 12/1999
JP 2002-240598 A 8/2002

(Continued)

Primary Examiner — Ryan Kwiecinski

(74) Attorney, Agent, or Firm — Morgan, Lewis & Bockius LLP

(57) **ABSTRACT**

A leg rest device may a first link member rotatably installed in a front of a seat frame, a second link member installed on a leg plate for supporting legs of a passenger and connected to the first link member to be movable along a longitudinal direction of the first link member, a guide member, one end of which is installed in the seat frame to be rotatable together with the first link member and the other end of which is connected to the second link member to be movable along a longitudinal direction of the second link member, and a driving portion installed in the seat frame. The driving portion, when operating, provides power for the first link member to be rotated, and allows the second link member to be rotated and simultaneously to be moved in the longitudinal direction of the first link member as the guide member is rotated together with the first link member.

7 Claims, 3 Drawing Sheets

