



US009410772B2

(12) **United States Patent**
Berroth et al.

(10) **Patent No.:** **US 9,410,772 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **BALLISTIC PROTECTION CONFIGURATION**

(75) Inventors: **Karl Berroth**, Frankenblick (DE);
Thomas Vorsatz, Suhl (DE)

(73) Assignee: **FCT Ingenieurkeramik GmbH**, Raunstein (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 202 days.

(21) Appl. No.: **14/123,417**

(22) PCT Filed: **May 29, 2012**

(86) PCT No.: **PCT/DE2012/000556**

§ 371 (c)(1),

(2), (4) Date: **Dec. 2, 2013**

(87) PCT Pub. No.: **WO2012/163329**

PCT Pub. Date: **Dec. 6, 2012**

(65) **Prior Publication Data**

US 2014/0116235 A1 May 1, 2014

(30) **Foreign Application Priority Data**

Jun. 1, 2011 (DE) 20 2011 101 638 U

(51) **Int. Cl.**

F41H 5/02 (2006.01)

F41H 5/04 (2006.01)

(52) **U.S. Cl.**

CPC **F41H 5/0414** (2013.01); **F41H 5/04**
(2013.01); **F41H 5/0428** (2013.01); **F41H**
5/0492 (2013.01)

(58) **Field of Classification Search**

USPC 89/36.02, 36.05, 36.01, 36.07; 2/2.5,
2/411

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,577,836 A * 5/1971 Tamura A41D 31/0061
2/2.5

8,215,223 B2 7/2012 Lucuta et al.

2001/0015157 A1* 8/2001 Neal B32B 3/06
109/49.5

2007/0172677 A1 7/2007 Biermann et al.

FOREIGN PATENT DOCUMENTS

DE 4005904 A1 8/1991

DE 60221849 T2 5/2008

DE 102007019392 A1 10/2008

WO 9208094 A1 5/1992

* cited by examiner

Primary Examiner — J. Woodrow Eldred

(74) *Attorney, Agent, or Firm* — Laurence A. Greenberg;
Werner H. Stemer; Ralph E. Locher

(57) **ABSTRACT**

A ballistic protection configuration includes a plurality of hard-armoring shaped elements which are formed as one piece and have at least two mutually offset planes. At least two of the shaped elements are fixed in a positional relationship with respect to one another in a shaped element composite in such a way that a first plane of a first shaped element overlaps in sections a second plane of a second shaped element. With the at least two overlapping planes of two shaped elements, two whole surfaces, which lie one above the other and offset with respect to one another, are formed in the shaped element composite and make it possible for a shaped element composite to be provided which is completely free of linear penetrations.

13 Claims, 4 Drawing Sheets

