US009510576B2

(12) **United States Patent**
Saito

(10) **Patent No.: US 9,510,576 B2**
(45) **Date of Patent: Dec. 6, 2016**

(54) **SPINNING REEL**

(71) Applicant: **Shimano Inc.**, Sakai, Osaka (JP)

(72) Inventor: **Kei Saito**, Osaka (JP)

(73) Assignee: **Shimano Inc.**, Osaka (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 175 days.

(21) Appl. No.: **14/520,709**

(22) Filed: **Oct. 22, 2014**

(65) **Prior Publication Data**

US 2015/0136889 A1 May 21, 2015

(30) **Foreign Application Priority Data**

Nov. 19, 2013 (JP) 2013-238561

(51) **Int. Cl.**
A01K 89/01 (2006.01)
A01K 89/015 (2006.01)
A01K 89/033 (2006.01)

(52) **U.S. Cl.**
CPC ***A01K 89/015*** (2013.01); ***A01K 89/0111*** (2013.01); ***A01K 89/033*** (2013.01)

(58) **Field of Classification Search**
CPC A01K 89/01; A01K 89/0111; A01K 89/011221; A01K 89/01928
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,149,089 A * 11/2000 Matsuda A01K 89/01 242/246
6,457,662 B1 * 10/2002 Sato A01K 89/01 242/247
2002/0117570 A1 * 8/2002 Kitajima A01K 89/0111 242/322
2003/0111569 A1 * 6/2003 Hitomi A01K 89/00 242/321
2005/0145735 A1 * 7/2005 Ikuta A01K 89/01 242/307
2006/0231657 A1 * 10/2006 Morise A01K 89/027 242/244
2008/0149750 A1 * 6/2008 Kitajima A01K 89/01 242/224
2009/0272831 A1 * 11/2009 Matsuo A01K 89/0111 242/322
2011/0042500 A1 * 2/2011 Saito A01K 89/01 242/224
2011/0180646 A1 * 7/2011 Hiraoka A01K 89/006 242/241

FOREIGN PATENT DOCUMENTS

JP 2002-204640 A 7/2002

* cited by examiner

Primary Examiner — Emmanuel M Marcelo
(74) *Attorney, Agent, or Firm* — Global IP Counselors

(57) **ABSTRACT**

The present spinning reel includes a reel body unit, a spool shaft, a spool, a drag mechanism, and a seal member. The spool includes a line winding cylinder part and a front flange. The drag mechanism includes a spool braking unit and a drag adjuster. The seal member is elastically deformable. The seal member protrudes from the drag adjuster side toward the front flange so as to close a space that is formed between the front flange and the drag adjuster. The seal member is configured to abut the front flange disposed on the front side of the line winding cylinder part.

8 Claims, 4 Drawing Sheets