

types of force feedback devices and is thus quite suitable for home consumer applications. A single actuator can be provided that directly applies force in the degree of freedom of a button of a mouse or to the command gesture motion of a pointing device such as a cylinder. The actuator does not output force in a main sensed degree of freedom of the device, thus allowing sensors to read the position of the user object without substantial interference from forces and also simplifying the control of output forces. Furthermore, the actuator of the present invention can provide a variety of different types of force sensations to enhance the user's experience and interface with a computer application.

These and other advantages of the present invention will become apparent to those skilled in the art upon a reading of the following specification of the invention and a study of the several figures of the drawing.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a mouse of the present invention connected to a host computer;

FIG. 2 is a side cross sectional view of the mouse of FIG. 1;

FIG. 3 is a side elevational view of a voice coil actuator suitable for use with the present invention;

FIG. 4 is a block diagram of the mouse and host computer of the present invention;

FIG. 5 is a diagrammatic view of a display screen showing graphical objects associated with force sensations output using the mouse of the present invention; and

FIGS. 6a and 6b are perspective and side elevational views, respectively, of a second pointing device of the present invention providing low cost force feedback.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

FIG. 1 is a perspective view of a force feedback mouse interface system 10 of the present invention capable of providing input to a host computer based on the user's manipulation of the mouse and capable of providing force feedback to the user of the mouse system based on events occurring in a program implemented by the host computer. Mouse system 10 includes a mouse 12 and a host computer 14. It should be noted that the term "mouse" as used herein, indicates an object generally shaped to be grasped or contacted from above and moved within a substantially planar workspace (and additional degrees of freedom if available). Typically, a mouse is a smooth or angular shaped compact unit that snugly fits under a user's hand, fingers, and/or palm, but can be implemented as a grip, finger cradle, cylinder, sphere, planar object, etc.

Mouse 12 is an object that is preferably grasped or gripped and manipulated by a user. By "grasp," it is meant that users may releasably engage a portion of the object in some fashion, such as by hand, with their fingertips, etc. In the described embodiment, mouse 12 is shaped so that a user's fingers or hand may comfortably grasp the object and move it in the provided degrees of freedom in physical space. For example, a user can move mouse 12 to provide planar two-dimensional input to a computer system to correspondingly move a computer generated graphical object, such as a cursor or other image, in a graphical environment provided by computer 14 or to control a virtual character, vehicle, or other entity in a game or simulation. In addition, mouse 12 preferably includes one or more buttons 16a and 16b to allow the user to provide additional com-

mands to the computer system. The mouse 12 may also include additional buttons. For example, a thumb button can be included on one side of the housing of mouse 12.

Mouse 12 preferably includes an actuator 18 which is operative to produce forces on one or more buttons of the mouse 12. This operation is described in greater detail below with reference to FIG. 2.

Mouse 12 rests on a ground surface 22 such as a tabletop or mousepad. A user grasps the mouse 12 and moves the mouse in a planar workspace on the surface 22 as indicated by arrows 24. Mouse 12 may be moved anywhere on the ground surface 22, picked up and placed in a different location, etc. A frictional ball and roller assembly (not shown) is provided on the underside of the mouse 12 to translate the motion of the mouse 12 into electrical position signals, which are sent to a host computer 14 over a bus 20 as is well known to those skilled in the art. In other embodiments, different mechanisms can be used to convert mouse motion to position or motion signals received by the host computer.

Mouse 12 is coupled to the computer 14 by a bus 20, which communicates signals between mouse 12 and computer 14 and may also, in some preferred embodiments, provide power to the mouse 12. Components such as actuator 18 require power that can be supplied from a conventional serial port or through an interface such as a USB or Firewire bus. In other embodiments, signals can be sent between mouse 12 and computer 14 by wireless transmission/reception.

Host computer 14 is preferably a personal computer or workstation, such as a PC compatible computer or Macintosh personal computer, or a Sun or Silicon Graphics workstation. For example, the computer 14 can operate under the Windows™, MacOS, Unix, or MS-DOS operating system. Alternatively, host computer system 14 can be one of a variety of home video game systems commonly connected to a television set, such as systems available from Nintendo, Sega, or Sony. In other embodiments, host computer system 14 can be a "set top box" which can be used, for example, to provide interactive television functions to users, or a "network-" or "internet-computer" which allows users to interact with a local or global network using standard connections and protocols such as used for the Internet and World Wide Web. Host computer preferably includes a host microprocessor, random access memory (RAM), read only memory (ROM), input/output (I/O) circuitry, and other components of computers well-known to those skilled in the art.

Host computer 14 preferably implements a host application program with which a user is interacting via mouse 12 and other peripherals, if appropriate, and which may include force feedback functionality. For example, the host application program can be a simulation, video game, Web page or browser that implements HTML or VRML instructions, scientific analysis program, virtual reality training program or application, or other application program that utilizes input of mouse 12 and outputs force feedback commands to the mouse 12. Herein, for simplicity, operating systems such as Windows™, MS-DOS, MacOS, Unix, etc. are also referred to as "application programs." In one preferred embodiment, an application program utilizes a graphical user interface (GUI) to present options to a user and receive input from the user. Herein, computer 14 may be referred as displaying "graphical objects" or "computer objects." These objects are not physical objects, but are logical software unit collections of data and/or procedures that may be displayed