US009409479B2

(12) **United States Patent**
Krauss

(10) **Patent No.: US 9,409,479 B2**
(45) **Date of Patent: Aug. 9, 2016**

(54) **SETTING DEVICE FOR MOTOR VEHICLE ASSISTANCE FUNCTION UNITS AND STEERING COLUMN LEVER OPERATOR CONTROL ASSEMBLY**

(71) Applicant: **Dr. Ing. h.c. F. Porsche Aktiengesellschaft**, Stuttgart (DE)

(72) Inventor: **Lutz Krauss**, Karlsruhe (DE)

(73) Assignee: **DR. ING. H.C. F. PORSCHE AKTIENGESELLSCHAFT**, Stuttgart (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 31 days.

(21) Appl. No.: **14/248,434**

(22) Filed: **Apr. 9, 2014**

(65) **Prior Publication Data**

US 2014/0316670 A1 Oct. 23, 2014

(30) **Foreign Application Priority Data**

Apr. 19, 2013 (DE) 10 2013 103 978

(51) **Int. Cl.**

G06F 7/70	(2006.01)
G06F 19/00	(2011.01)
G06G 7/00	(2006.01)
G06G 7/76	(2006.01)
B60T 8/32	(2006.01)
G05D 1/00	(2006.01)
G06F 7/00	(2006.01)
G06F 17/00	(2006.01)
B60K 31/00	(2006.01)
B60W 30/14	(2006.01)
B60W 30/16	(2012.01)

(52) **U.S. Cl.**

CPC ***B60K 31/00*** (2013.01); *B60K 2310/20* (2013.01); *B60W 30/143* (2013.01); *B60W 30/146* (2013.01); *B60W 30/16* (2013.01); *Y02T 10/84* (2013.01)

(58) **Field of Classification Search**

CPC B60K 2310/00; B60K 2310/20

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,665,026	A	9/1997	Linden	
5,713,428	A	2/1998	Linden et al.	
2003/0195704	A1 *	10/2003	Sekiguchi	B60W 30/16 701/301
2007/0255479	A1 *	11/2007	Gruenter	B60K 31/042 701/93
2008/0270001	A1 *	10/2008	Seto	B60K 31/00 701/93

FOREIGN PATENT DOCUMENTS

DE	19509492	C2	9/1996
DE	19509494	C2	9/1996
DE	102006017330	U1	10/2006
DE	102006028463	A1	12/2007
JP	H 115456	A	1/1999
JP	2007015558	A	1/2007

* cited by examiner

Primary Examiner — Yonel Beaulieu
Assistant Examiner — Lail Kleinman
(74) *Attorney, Agent, or Firm* — Leydig, Voit & Mayer, Ltd.

(57) **ABSTRACT**

A device is configured for setting at least three assistance function units that influence the speed of a motor vehicle. The assistance function units are selected from a group consisting of a speed maintaining assistance function unit, a predictive distance control assistance function unit, a speed limiting assistance function unit, and an uphill or downhill travel assistance function unit. The device includes an individual switching operator control unit and a control unit configured to monitor the actuation of the individual switching operator control unit, and select an assistance function unit when the individual switching operator control unit is activated.

10 Claims, 2 Drawing Sheets