US009411181B2

(12) **United States Patent**
Vissenberg et al.

(10) **Patent No.: US 9,411,181 B2**
(45) **Date of Patent: Aug. 9, 2016**

(54) **DISPLAY DEVICE**

(75) Inventors: **Michel Cornelis Josephus Marie Vissenberg**, Eindhoven (NL); **Willem Lubertus Ijzerman**, Eindhoven (NL); **Gabriela Binasch**, Eindhoven (NL)

(73) Assignee: **KONINKLIJKE PHILIPS N.V.**, Eindhoven (NL)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1448 days.

(21) Appl. No.: **12/067,304**

(22) PCT Filed: **Sep. 13, 2006**

(86) PCT No.: **PCT/IB2006/053251**

§ 371 (c)(1), (2), (4) Date: **Mar. 19, 2008**

(87) PCT Pub. No.: **WO2007/034370**

PCT Pub. Date: **Mar. 29, 2007**

(65) **Prior Publication Data**

US 2008/0258995 A1 Oct. 23, 2008

(30) **Foreign Application Priority Data**

Sep. 21, 2005 (EP) 05108700

(51) **Int. Cl.**

G09G 5/00	(2006.01)
G02F 1/13	(2006.01)
B60K 35/00	(2006.01)
G02F 1/1335	(2006.01)
B60R 11/00	(2006.01)
F21V 8/00	(2006.01)
G02F 1/1333	(2006.01)

(52) **U.S. Cl.**

CPC ***G02F 1/1323*** (2013.01); ***B60K 35/00*** (2013.01); ***G02F 1/133615*** (2013.01); *B60K 2350/901* (2013.01); *B60K 2350/903* (2013.01); *B60R 2011/0005* (2013.01); *G02B 6/0043* (2013.01); *G02B 6/0051* (2013.01); *G02F 2001/133391* (2013.01)

(58) **Field of Classification Search**

CPC G06F 19/22; G06F 19/345; G06F 1/163
USPC 345/1, 102, 7, 9; 349/64, 66, 62, 65
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,371,510	A *	12/1994	Miyauchi et al.	345/7
5,897,184	A *	4/1999	Eichenlaub et al.	349/64
6,231,201	B1	5/2001	Rupp	
6,337,721	B1	1/2002	Hamagishi et al.	

(Continued)

FOREIGN PATENT DOCUMENTS

EP	0896897	A2	2/1999
GB	2404991	A	2/2005

(Continued)

Primary Examiner — Olga Merkoulova
(74) *Attorney, Agent, or Firm* — Larry Liberchuk

(57) **ABSTRACT**

The present invention relates to a dual view display device where a display surface is divided into a first and a second sub-section (**10***a*, **10***b*). A backlighting arrangement is used which provides light with different angular distributions (**16***a*, **16***b*; **16***a*', **16***b*') to the different sub-sections. This allows at low cost e.g. in a vehicle the displaying of movies or computer game windows at a part of a display, which part is not visible for the driver of the vehicle.

9 Claims, 3 Drawing Sheets