



US009410986B2

(12) **United States Patent**
Ku et al.

(10) **Patent No.:** **US 9,410,986 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **TESTING JIG**

(56) **References Cited**

(71) Applicant: **MPI CORPORATION**, Zhubei (TW)

U.S. PATENT DOCUMENTS

(72) Inventors: **Wei-Cheng Ku**, Zhubei (TW); **Hao Wei**, Zhubei (TW); **Chia-Nan Chou**, Zhubei (TW); **Chih-Hao Ho**, Zhubei (TW)

4,765,471 A *	8/1988	Murphy	G01R 1/0483 206/489
4,825,155 A *	4/1989	Takamine	G01R 1/04 324/756.05
4,866,374 A *	9/1989	Cedrone	G01R 1/0433 324/537
5,847,572 A *	12/1998	Iwasaki	G01R 1/0433 324/754.08
5,975,915 A *	11/1999	Yamazaki	G01R 1/0433 439/331
7,825,677 B2 *	11/2010	Takemoto	G01R 31/2886 324/762.02
2009/0311890 A1 *	12/2009	Nakayama	G01R 1/07371 439/91
2010/0052722 A1 *	3/2010	Takemoto	G01R 31/2886 324/754.06
2011/0248737 A1 *	10/2011	Takeshita	G01R 31/2889 324/756.02
2012/0115366 A1 *	5/2012	Suzuki	G01R 1/0466 439/626

(73) Assignee: **MPI CORPORATION**, Zhubei (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 64 days.

(21) Appl. No.: **14/557,879**

(22) Filed: **Dec. 2, 2014**

(65) **Prior Publication Data**

US 2015/0204905 A1 Jul. 23, 2015

* cited by examiner

Primary Examiner — Arleen M Vazquez

Assistant Examiner — Alesa Allgood

(30) **Foreign Application Priority Data**

Dec. 13, 2013 (TW) 102146097 A

(74) *Attorney, Agent, or Firm* — Terry M. Heims; Apex Juris, PLLC

(51) **Int. Cl.**
G01R 1/04 (2006.01)

(57) **ABSTRACT**

A testing jig includes a substrate, a carrier provided on the substrate, two conductive members made of a conductive material, and a compensation member made of a conductive material. The substrate has a signal circuit and a grounding circuit thereon. The carrier has a base board made of an insulating material and a conductive circuit made of a conductive material provided thereon. The base board has a signal perforation aligning with the signal circuit, a grounding perforation aligning with the grounding circuit, and multiple compensation holes. The conductive members both have an end exposed out of the carrier, and are respectively fitted in the signal perforation and the grounding perforation to make another end thereof contact the signal circuit or the grounding circuit. The compensation member is fitted in one of the compensation holes to be electrically connected to the conductive member in the grounding perforation through the conductive circuit.

(52) **U.S. Cl.**
CPC **G01R 1/0466** (2013.01)

(58) **Field of Classification Search**
CPC G01R 1/0466; G01R 1/0483; G01R 31/2893; G01R 1/0408; G01R 1/0433; G01R 31/2886; G01R 1/0441; G01R 3/00; G01R 1/067; G01R 1/06738; G01R 1/06711; G01R 1/07307; G01R 1/06761; G01R 1/07378; G01R 1/06755; G01R 1/06772; G01R 1/06788; G01R 1/06794; G01R 1/073; G01R 1/07314

See application file for complete search history.

8 Claims, 5 Drawing Sheets

