



(12) **United States Patent**
Hearn et al.

(10) **Patent No.:** **US 9,408,987 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **INHALER**
(75) Inventors: **Alex Hearn**, London (GB); **Iain McDerment**, Royston (GB)
(73) Assignee: **Kind Consumer Limited**, London (GB)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 953 days.

USPC 128/202.21, 200.21, 203.12, 203.23, 128/203.16, 203.17; 131/273, 194, 271, 131/329, 330, 360
See application file for complete search history.

(21) Appl. No.: **13/389,434**
(22) PCT Filed: **Aug. 6, 2010**

(56) **References Cited**
U.S. PATENT DOCUMENTS
3,631,856 A 1/1972 Taylor
4,393,884 A 7/1983 Jacobs
(Continued)

(86) PCT No.: **PCT/GB2010/001487**
§ 371 (c)(1),
(2), (4) Date: **Feb. 7, 2012**

FOREIGN PATENT DOCUMENTS

FR 1601834 A 9/1970
WO 0245783 A1 6/2002
(Continued)

(87) PCT Pub. No.: **WO2011/015825**
PCT Pub. Date: **Feb. 10, 2011**

OTHER PUBLICATIONS

International search report for application No. PCT/GB2010/001487 dated Nov. 23, 2010.

(65) **Prior Publication Data**
US 2012/0138052 A1 Jun. 7, 2012

(Continued)

(30) **Foreign Application Priority Data**
Aug. 7, 2009 (GB) 0913942.9
Jan. 11, 2010 (GB) 1000403.4
Feb. 8, 2010 (GB) 1002024.6

Primary Examiner — Tan-Uyen (Jackie) T Ho
Assistant Examiner — Mark Wardas
(74) *Attorney, Agent, or Firm* — Patterson & Sheridan, LLP

(51) **Int. Cl.**
A61M 15/06 (2006.01)
A61M 15/00 (2006.01)
(Continued)

(57) **ABSTRACT**
An inhaler comprising a reservoir of an inhalable composition with an outlet at one end through which the inhalable composition is discharged. A non-metered breath-activated valve is provided between the one end and the reservoir, the breath-activated valve comprising a flow path extending from the reservoir to the outlet end. At least a portion of the flow path is a deformable tube. A clamping member pinches the deformable tube closed when no suction force is applied to the device and releases the tube to open the flow path when suction is applied at the outlet, to provide uninterrupted flow from the reservoir to the outlet.

(52) **U.S. Cl.**
CPC **A61M 15/0091** (2013.01); **A24F 47/002** (2013.01); **A61M 15/0093** (2014.02); **A61M 15/06** (2013.01); **A61M 16/20** (2013.01); **A61M 2205/8225** (2013.01)

(58) **Field of Classification Search**
CPC A61M 15/0091; A61M 15/0093; A61M 15/06; A61M 16/20; A61M 2205/8225; A24F 47/002

13 Claims, 6 Drawing Sheets

