



US007151787B2

(12) **United States Patent**  
**Kulp et al.**

(10) **Patent No.:** **US 7,151,787 B2**

(45) **Date of Patent:** **Dec. 19, 2006**

(54) **BACKSCATTER ABSORPTION GAS IMAGING SYSTEMS AND LIGHT SOURCES THEREFORE**

5,430,293 A 7/1995 Sato et al.  
5,434,700 A 7/1995 Yoo  
5,656,813 A 8/1997 Moore et al.  
5,864,644 A 1/1999 DiGiovanni et al.

(75) Inventors: **Thomas Jan Kulp**, Livermore, CA (US); **Dahv A. V. Kliner**, San Ramon, CA (US); **Ricky Sommers**, Oakley, CA (US); **Uta-Barbara Goers**, Campbell, NY (US); **Karla M. Armstrong**, Livermore, CA (US)

(Continued)

**FOREIGN PATENT DOCUMENTS**

EP 0 857 997 B1 10/2001

(Continued)

**OTHER PUBLICATIONS**

(73) Assignee: **Sandia National Laboratories**, Livermore, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 199 days.

Goers et al., Development of a compact gas imaging sensor employing a cw fiber-amp pumped PPLN OPO technical paper during CLEO 2001 sent in by IDS on Oct. 20, 2003.\*

(Continued)

(21) Appl. No.: **10/658,906**

(22) Filed: **Sep. 10, 2003**

*Primary Examiner*—Minsun Oh Harvey  
*Assistant Examiner*—Dung (Michael) T. Nguyen  
(74) *Attorney, Agent, or Firm*—Steven R. Vosen

(65) **Prior Publication Data**

US 2005/0053104 A1 Mar. 10, 2005

(57) **ABSTRACT**

(51) **Int. Cl.**

**H01S 3/091** (2006.01)

(52) **U.S. Cl.** ..... **372/70; 372/20; 372/22; 372/6**

(58) **Field of Classification Search** ..... **372/6, 372/20, 21, 22, 70**

See application file for complete search history.

The location of gases that are not visible to the unaided human eye can be determined using tuned light sources that spectroscopically probe the gases and cameras that can provide images corresponding to the absorption of the gases. The present invention is a light source for a backscatter absorption gas imaging (BAGI) system, and a light source incorporating the light source, that can be used to remotely detect and produce images of "invisible" gases. The inventive light source has a light producing element, an optical amplifier, and an optical parametric oscillator to generate wavelength tunable light in the IR. By using a multi-mode light source and an amplifier that operates using 915 nm pump sources, the power consumption of the light source is reduced to a level that can be operated by batteries for long periods of time. In addition, the light source is tunable over the absorption bands of many hydrocarbons, making it useful for detecting hazardous gases.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,609,398 A	9/1971	Bjorkholm	307/88.3
3,628,186 A	12/1971	Rumson et al.	331/107 R
3,948,345 A	4/1976	Rosencwaig	181/0.5
4,555,627 A	11/1985	McRae, Jr.	
4,622,845 A	11/1986	Ryan et al.	73/24
4,745,276 A	5/1988	Broicher et al.	
5,097,477 A *	3/1992	Scheps	372/94
5,117,126 A	5/1992	Geiger	359/330
5,202,560 A	4/1993	Kock et al.	356/435

**90 Claims, 5 Drawing Sheets**

