

11

the breakaway wrist strap comprises an adjustable band, a strap fastener, and a second snap buckle;

the lateral protective surface comprises an exterior lateral surface and an interior lateral surface;

both the first sleeve opening and the second sleeve opening each comprise a width adjuster mechanism and a breakaway recovery strap;

the width adjuster mechanism comprises a drawstring, a drawstring channel, and a drawstring lock;

the breakaway recovery strap comprises a loop strap and a first snap buckle;

the drawstring comprises a first drawstring end and a second drawstring end;

the channel comprises channel opening;

the extendable sleeve being detachably engaged to the breakaway wrist strap, wherein the detachable engagement between the extendable sleeve and the breakaway wrist strap is provided as a low jerk detachable engagement;

the first sleeve opening being terminally positioned on the extendable sleeve;

the second sleeve opening being terminally positioned on the extendable sleeve opposite the first sleeve opening;

the lateral protective surface being positioned between the first sleeve opening and the second sleeve opening;

the first sleeve opening, the lateral protective surface, and the second sleeve opening being centrally aligned, wherein the central alignment between the first sleeve opening, the lateral protective surface and the second sleeve opening traverse along the length of the extendable sleeve providing an interior channel for a rope;

the interior lateral surface being positioned concentric to the exterior lateral surface;

the exterior lateral surface being peripherally positioned to the extendable sleeve opposite the interior lateral surface;

the width adjuster mechanism of the first sleeve opening being circumferentially positioned to the first sleeve opening;

the width adjuster mechanism of the second sleeve opening being circumferentially positioned to the second sleeve opening;

the breakaway recovery strap of the first opening being tangentially positioned to the width adjuster mechanism of the first sleeve opening;

12

the breakaway recovery strap of the second sleeve opening being tangentially positioned to the width adjuster mechanism of the second sleeve opening;

the lateral protective surface being compressible between the first sleeve opening and the second sleeve opening;

the breakaway recovery strap of the first sleeve opening being extendably coupled to the lateral protective surface by way of the width adjuster mechanism of the first sleeve opening; and

the breakaway recovery strap of the second sleeve opening being extendably coupled to the lateral protective surface by way of the width adjuster mechanism of the second sleeve opening.

14. The extendable rope protecting sleeve as claimed in claim 13 comprises:

the width adjuster mechanism being coincident with the lateral protective surface;

the drawstring channel being positioned between the exterior lateral surface and the interior lateral surface;

the drawstring channel being traversed by the drawstring by way of the channel openings;

the first drawstring end and the second drawstring end being peripherally positioned to the drawstring channel;

both the first drawstring end and the second drawstring end traverse the drawstring lock;

the drawstring lock being proximally positioned to the channel openings;

the breakaway recovery strap being coupled peripherally to the width adjuster mechanism opposite the drawstring lock;

the loop strap being distally positioned to the width adjuster mechanism;

the first snap buckle being peripherally positioned on the breakaway recovery strap adjacent to the loop strap;

the first snap buckle being detachably engaged to the breakaway wrist strap by way of the second snap buckle;

the breakaway wrist strap being detachably engaged to the breakaway recovery strap;

the adjustable band being securable by the strap fastener, wherein the adjustable band is securable to a user by way of the strap fastener;

the second snap buckle being peripherally positioned on the adjustable band; and

the second snap buckle being detachably engaged to breakaway recovery strap by way of the first snap buckle.

* * * * *