



US009409191B2

(12) **United States Patent**
Walter

(10) **Patent No.:** **US 9,409,191 B2**

(45) **Date of Patent:** ***Aug. 9, 2016**

(54) **INTERNAL MIXING SPRAY GUN**

(2013.01); **B01F 5/0615** (2013.01); **B01F 5/0682** (2013.01); **B01F 5/0688** (2013.01); **B05B 15/025** (2013.01); **B29B 7/7438** (2013.01); **B01F 2005/0034** (2013.01); **B05B 7/0408** (2013.01)

(71) Applicant: **Carlisle Fluid Technologies, Inc.**,
Charlotte, NC (US)

(72) Inventor: **Bradley P. Walter**, Superior, CO (US)

(58) **Field of Classification Search**
CPC .. B05B 7/2455; B05B 7/0416; B05B 7/0441; B05B 7/1209; B05B 7/2478
USPC 239/419, 424.5, 427, 433, 413, 569, 239/498, 398
See application file for complete search history.

(73) Assignee: **Carlisle Fluid Technologies, Inc.**,
Charlotte, NC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,297,305 A	1/1967	VValden
3,506,460 A	4/1970	Bayne
3,709,468 A	1/1973	Ives
3,759,450 A	9/1973	Fram et al.
3,790,030 A	2/1974	Ives

(Continued)

(21) Appl. No.: **14/287,100**

(22) Filed: **May 26, 2014**

(65) **Prior Publication Data**

US 2014/0252121 A1 Sep. 11, 2014

FOREIGN PATENT DOCUMENTS

DE	7733456 U1	5/1978
GB	1236883	6/1971

(Continued)

Related U.S. Application Data

(63) Continuation of application No. 13/675,504, filed on Nov. 13, 2012, now Pat. No. 8,757,515, which is a continuation of application No. 12/502,527, filed on Jul. 14, 2009, now Pat. No. 8,322,632.

Primary Examiner — Davis Hwu
(74) *Attorney, Agent, or Firm* — Fletcher Yoder, P.C.

(51) **Int. Cl.**

F23D 11/16	(2006.01)
B05B 7/02	(2006.01)
B01F 5/02	(2006.01)
B01F 5/06	(2006.01)
B29B 7/74	(2006.01)
B05B 15/02	(2006.01)
B01F 5/00	(2006.01)
B05B 7/04	(2006.01)

(57) **ABSTRACT**

A system, in certain embodiments, includes a spray device including a first liquid passage configured to flow a first liquid in a generally downstream direction toward a spray tip. The spray device also includes a second liquid passage configured to flow a second liquid in a generally upstream direction such that the second liquid impinges upon the first liquid at an outlet to the second liquid passage. The upstream direction is substantially opposite from the downstream direction.

(52) **U.S. Cl.**

CPC **B05B 7/02** (2013.01); **B01F 5/0256**

20 Claims, 9 Drawing Sheets

