US009409391B2

(12) **United States Patent**
Kim et al.

(10) **Patent No.: US 9,409,391 B2**
(45) **Date of Patent: Aug. 9, 2016**

(54) **METHODS OF DRIVING HYBRID INKJET PRINTING APPARATUS INCLUDING RESONATING INK IN A NOZZLE**

(75) Inventors: **Joong-hyuk Kim**, Seoul (KR); **Young-ki Hong**, Anyang-si (KR); **Jae-woo Chung**, Seoul (KR)

(73) Assignee: **Samsung Electronics Co., Ltd.**, Gyeonggi-Do (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 499 days.

(21) Appl. No.: **13/568,604**

(22) Filed: **Aug. 7, 2012**

(65) **Prior Publication Data**

US 2013/0176354 A1 Jul. 11, 2013

(30) **Foreign Application Priority Data**

Jan. 11, 2012 (KR) 10-2012-0003456

(51) **Int. Cl.**

B41J 29/38	(2006.01)
B41J 2/045	(2006.01)
B41J 2/06	(2006.01)
B41J 2/14	(2006.01)

(52) **U.S. Cl.**

CPC ***B41J 2/04581*** (2013.01); ***B41J 2/04588*** (2013.01); ***B41J 2/06*** (2013.01); ***B41J 2/14233*** (2013.01)

(58) **Field of Classification Search**

CPC B41J 2/04581; B41J 2/06; B41J 2/14233; B41J 2/04588

USPC 347/10, 48, 47

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,023,625	A *	6/1991	Bares et al.	347/48
5,477,249	A *	12/1995	Hotomi	347/48
6,092,886	A	7/2000	Hosono	
6,106,092	A *	8/2000	Norigoe et al.	347/11
6,629,741	B1	10/2003	Okuda et al.	
6,799,821	B1 *	10/2004	Okuda	347/10
7,314,185	B2	1/2008	Nishi et al.	
7,905,578	B2 *	3/2011	Nishi	B41J 2/14314 347/47
8,342,623	B2 *	1/2013	Hong et al.	347/10

(Continued)

FOREIGN PATENT DOCUMENTS

JP	2004-202893 A	7/2004
JP	2009-073074 A	4/2009
JP	2010-006048 A	1/2010

OTHER PUBLICATIONS

"On-demand electrohydrodynamic jetting with meniscus control by a piezoelectric actuator for ultra-fine patterns" Young-Jae Kim et al 2009 J. Micromech. Microeng. 19 107001 doi:10.1088/0960-1317/19/10/107001.*

Primary Examiner — Stephen Meier
Assistant Examiner — John P Zimmermann
(74) *Attorney, Agent, or Firm* — Harness, Dickey & Pierce, P.L.C.

(57) **ABSTRACT**

A method of driving a hybrid inkjet printing apparatus includes applying an electrostatic voltage to ink contained in a nozzle, applying a waveform voltage to ink contained in the nozzle, the waveform voltage being applied by a piezoelectric driving device, and applying an ejection voltage so as to eject the ink.

16 Claims, 7 Drawing Sheets