

source to supply compressed air to drive the pneumatic dispenser.

15. The fluid dispensing system of claim 13 comprising:

the manual fluid pump including a cylinder with a biased piston slidably received in the cylinder, the piston being adapted to be manually retracted from the cylinder to fill the cylinder with fluid drawn from the fluid source, and to be biased back into the cylinder to force the drawn fluid out of the cylinder at the first pressure.

16. The fluid dispensing system of claim 13 comprising:

the pneumatic dispenser including a barrel adapted to receive the fluid supplied by the manual fluid pump, and a plunger slidably received in the barrel, the plunger being adapted to selectively slide through the barrel and forcibly dispense from the barrel fluid received by the barrel, the fluid being dispensed from the barrel at the second pressure, greater than the first pressure.

17. The fluid dispensing system of claim 16 comprising:

the pneumatic dispenser including a chamber adapted to selectively receive compressed air from a compressed air source, and a piston slidably received in the chamber and connected with the plunger, the piston being adapted to slide the plunger through

5

10

15

20

25

30

35

40

45

50

55

60

65

the barrel in response to compressed air being received in the chamber.

18. A combined manual and pneumatic fluid dispensing system comprising:

a self contained fluid pump adapted to be placed in fluid communication with a source of fluid and to both draw fluid from the source and deliver the drawn fluid under pressure;

a fluid dispensing gun adapted to receive fluid at a first pressure and to receive compressed air, and to selectively dispense a predetermined quantity of fluid received by the gun at a second pressure greater than the first pressure;

a first fluid communication means communicating the fluid dispensing gun with the fluid pump; and

a second fluid communication means communicating the fluid dispensing gun with a source of compressed air;

the fluid pump being a manually primed pump having a cylinder with a manually displaceable piston slidably received in the cylinder and a spring between the piston and cylinder, the piston being adapted to be manually displaced against the spring bias to a first position to draw fluid into the cylinder and prime the pump, and the piston being adapted to be displaced to a second position by the bias of the spring to force fluid drawn into the cylinder out of the cylinder and into the first fluid communication means.

* * * * *