US009535493B2

(12) **United States Patent**
Guo et al.

(10) **Patent No.: US 9,535,493 B2**
(45) **Date of Patent: Jan. 3, 2017**

(54) **APPARATUS, METHOD, COMPUTER PROGRAM AND USER INTERFACE**

(75) Inventors: **Yongguang Guo**, Beijing (CN); **Shiming Ge**, Beijing (CN)

(73) Assignee: **Nokia Technologies Oy**, Espoo (FI)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 24 days.

(21) Appl. No.: **13/640,654**

(22) PCT Filed: **Apr. 13, 2010**

(86) PCT No.: **PCT/CN2010/071718**

§ 371 (c)(1),
(2), (4) Date: **Oct. 11, 2012**

(87) PCT Pub. No.: **WO2011/127646**

PCT Pub. Date: **Oct. 20, 2011**

(65) **Prior Publication Data**

US 2013/0033459 A1 Feb. 7, 2013

(51) **Int. Cl.**

G06F 3/01	(2006.01)
G06F 3/0346	(2013.01)
G06F 3/0481	(2013.01)

(52) **U.S. Cl.**

CPC ***G06F 3/011*** (2013.01); ***G06F 3/017*** (2013.01); ***G06F 3/0346*** (2013.01); ***G06F 3/04815*** (2013.01)

(58) **Field of Classification Search**

CPC G06F 3/011; G06F 3/017; G06F 3/0346; G06F 3/04815

USPC 345/175, 173

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,483,261	A	1/1996	Yasutake	
6,043,818	A *	3/2000	Nakano	G06F 3/04815 345/473
6,198,485	B1	3/2001	Mack	
6,624,833	B1	9/2003	Kumar	
7,512,902	B2 *	3/2009	Robertson	G06F 3/0481 715/782
7,823,089	B2 *	10/2010	Wilson	715/863
8,094,120	B2 *	1/2012	Ratai	345/156
8,166,421	B2 *	4/2012	Magal et al.	715/863

(Continued)

FOREIGN PATENT DOCUMENTS

CN	101344816	1/2009
WO	WO-03/079179	9/2003

OTHER PUBLICATIONS

Grossman, T., Wigdor, D. and Balakrishnan, R. Multi-Finger Gestural Interaction with 3D Volumetric Displays. Proc. UIST '04, 2004, pp. 61-70.*

(Continued)

Primary Examiner — Dmitriy Bolotin
(74) *Attorney, Agent, or Firm* — Alston & Bird LLP

(57) **ABSTRACT**

An apparatus, method, computer program and apparatus wherein the apparatus comprises: at least one processor: and at least one memory including computer program code; wherein the at least one memory and the computer program code are configured to, with the at least one processor, enable the apparatus to; detect, using a camera, motion of a user input object; and determine, for performance, a function corresponding to the detected motion of the user input object wherein the function comprises control of an entity within a three dimensional model.

20 Claims, 5 Drawing Sheets