US009636894B2

(12) **United States Patent**
Lu

(10) **Patent No.: US 9,636,894 B2**
(45) **Date of Patent: *May 2, 2017**

(54) **POLYMER INTERLAYERS COMPRISING A BLEND OF TWO OR MORE RESINS**

(71) Applicant: **SOLUTIA INC.**, St. Louis, MO (US)

(72) Inventor: **Jun Lu**, East Longmeadow, MA (US)

(73) Assignee: **Solutia Inc.**, St. Louis, MO (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/973,547**

(22) Filed: **Dec. 17, 2015**

(65) **Prior Publication Data**

US 2016/0102181 A1 Apr. 14, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/300,612, filed on Jun. 10, 2014, now Pat. No. 9,248,626.

(60) Provisional application No. 61/833,205, filed on Jun. 10, 2013.

(51) **Int. Cl.**

C08J 5/18	(2006.01)
B32B 27/22	(2006.01)
B32B 7/02	(2006.01)
B32B 27/08	(2006.01)
B32B 27/30	(2006.01)
C08L 29/14	(2006.01)
C08K 5/00	(2006.01)
C08L 29/04	(2006.01)
C08K 5/11	(2006.01)
C08K 5/12	(2006.01)
C08K 5/13	(2006.01)
B32B 17/10	(2006.01)

(52) **U.S. Cl.**

CPC ***B32B 27/22*** (2013.01); ***B32B 7/02*** (2013.01); ***B32B 17/10036*** (2013.01); ***B32B 17/1055*** (2013.01); ***B32B 17/10605*** (2013.01); ***B32B 17/10761*** (2013.01); ***B32B 27/08*** (2013.01); ***B32B 27/30*** (2013.01); ***B32B 27/306*** (2013.01); ***C08J 5/18*** (2013.01); ***C08K 5/0016*** (2013.01); ***C08K 5/11*** (2013.01); ***C08K 5/12*** (2013.01); ***C08K 5/13*** (2013.01); ***C08L 29/04*** (2013.01); ***C08L 29/14*** (2013.01); *B32B 2250/02* (2013.01); *B32B 2250/03* (2013.01); *B32B 2250/246* (2013.01); *B32B 2307/412* (2013.01); *B32B 2307/418* (2013.01); *B32B 2307/546* (2013.01); *B32B 2307/558* (2013.01); *B32B 2307/56* (2013.01); *B32B 2329/06* (2013.01); *B32B 2419/00* (2013.01); *B32B 2457/12* (2013.01); *B32B 2605/08* (2013.01); *B32B 2605/18* (2013.01); *C08J 2329/14* (2013.01); *C08L 2205/02* (2013.01); *C08L 2205/025* (2013.01); *Y10T 428/24983* (2015.01)

(58) **Field of Classification Search**

CPC B32B 17/10036; B32B 17/1055; B32B 17/10605; B32B 17/10761; B32B 2250/02; B32B 2250/03; B32B 2250/246; B32B 2307/56; B32B 2307/412; B32B 2307/418; B32B 2307/546; B32B 2307/558; B32B 2329/06; B32B 2419/00; B32B 2457/12; B32B 2605/08; B32B 2605/18; B32B 27/02; B32B 27/08; B32B 27/22; B32B 27/30; B32B 27/306; B32B 7/02; C08J 2329/14; C08J 5/18; C08K 5/11; C08K 5/12; C08K 5/13; C08L 2205/02; C08L 2205/025; C08L 29/04; C08L 29/14

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,282,026 A	5/1942	Bozetech Bren et al.	
2,282,057 A	5/1942	Hopkins et al.	
2,456,366 A	12/1948	Bren et al.	
3,644,594 A	2/1972	Mont	
4,361,625 A	11/1982	Beckmann et al.	
4,584,229 A	4/1986	Bourelier et al.	
4,874,814 A	10/1989	Cartier	
5,169,897 A	12/1992	Walls	
5,190,826 A *	3/1993	Asahina	B32B 17/10009 181/176
5,290,660 A	3/1994	Eian et al.	
5,340,654 A	8/1994	Ueda et al.	
5,409,734 A	4/1995	Lee et al.	
5,593,786 A	1/1997	Parker et al.	
5,728,472 A	3/1998	D'Errico	
6,372,352 B1	4/2002	Bletsos et al.	

(Continued)

FOREIGN PATENT DOCUMENTS

DE	10343385 A1	4/2005
DE	102008001512 A1	11/2009

(Continued)

OTHER PUBLICATIONS

http://www.chemicalbook.com/ChemicalProductProperty_EN_CB0225180.htm; Jul. 2011.

Dupont, Untitled [discloses comparisons between PVB and SGP interlayers used in safety glass], accessed on Sep. 12, 2016, Dupont.com, obtained from http://www2.dupont.com/Building_Innovations/zh_CN/assets/downloads/SGPintro_E.pdf.

PubChem, Glutaraldehyde, accessed on Sep. 12, 2016, NIH.gov, obtained from https://pubchem.ncbi.nlm.nih.gov/compound/glotaraldehyde#section=Top.

(Continued)

Primary Examiner — Satya Sastri

(74) *Attorney, Agent, or Firm* — Michelle Bugbee

(57) **ABSTRACT**

An interlayer comprised of a blend of thermoplastic resins and at least one high refractive index having improved acoustic and optical quality is disclosed. The use of a blend thermoplastic resins and a high refractive index plasticizer improves transparency and acoustic properties without sacrificing other characteristics of the interlayer.

19 Claims, No Drawings