

(12) **United States Patent**
Gugerli et al.

(10) **Patent No.:** **US 9,408,495 B2**
(45) **Date of Patent:** ***Aug. 9, 2016**

(54) **DEVICE AND METHOD FOR PRODUCING A FROTHED LIQUID FROM SOLUBLE INGREDIENTS AND DILUENT**

(71) Applicant: **NESTEC S.A., Vevey (CH)**

(72) Inventors: **Raphael Gugerli, Genolier (CH); Jean-Luc Thuliez, Le Landeron (CH); Iwan Kissling, Bienne (CH); Raphael Bernhardsgruetter, St. Gallen (CH); Cedric Beausire, Bavois (CH); Nihan Dogan, La Croix-sur-Lutry (CH); David J. Harrison, New Milford, CT (US); David Hamel, Chemex (CH)**

(73) Assignee: **Nestec S.A., Vevey (CH)**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/588,764**

(22) Filed: **Jan. 2, 2015**

(65) **Prior Publication Data**

US 2015/0110936 A1 Apr. 23, 2015

Related U.S. Application Data

(62) Division of application No. 12/518,675, filed as application No. PCT/EP2007/063391 on Dec. 6, 2007, now Pat. No. 8,960,079.

(30) **Foreign Application Priority Data**

Dec. 11, 2006 (EP) 06125772

(51) **Int. Cl.**

A23F 3/00 (2006.01)
A47G 19/14 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A47J 31/46** (2013.01); **A23F 5/262** (2013.01); **A23L 2/54** (2013.01); **A47J 31/401** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC **A47J 31/401; A47J 31/402; A47J 31/404; A47J 31/405**

USPC **99/323, 323.1, 323.3, 279, 293-295; 426/474, 477, 590-597**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,522,102 A * 9/1950 Dold **A47J 31/06**
366/165.1

3,212,757 A 10/1965 Martin

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0449533 10/1991
EP 0885580 12/1998

(Continued)

OTHER PUBLICATIONS

International Search Report for International Application No. PCT/EP2007/063391 mailed on Mar. 4, 2008.

(Continued)

Primary Examiner — Tu B Hoang

Assistant Examiner — Alba Rosario-Aponte

(74) *Attorney, Agent, or Firm* — K&L Gates LLP

(57) **ABSTRACT**

Device for producing a frothed liquid comprising a chamber opened to atmosphere with a transverse bottom wall and a longitudinal upward wall, at least one diluent inlet, at least one liquid delivery outlet. The diluent inlet is provided through the upward wall and is dimensioned and oriented for directing a thin jet of diluent in the chamber. The at least one liquid delivery outlet is configured in the bottom wall for liquid to rise up along the side of the upward wall by the jet of diluent entering the chamber as a result of the direction and dimension of the diluent inlet in the chamber.

12 Claims, 12 Drawing Sheets

