



US009409198B2

(12) **United States Patent**
Hosokawa et al.

(10) **Patent No.:** **US 9,409,198 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **METHOD AND APPARATUS FOR APPLYING COATING SOLUTION, AND METHOD FOR MANUFACTURING COATED PRODUCT**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(75) Inventors: **Toshitsugu Hosokawa**, Ibaraki (JP); **Keichi Okamoto**, Ibaraki (JP); **Satoru Yamamoto**, Ibaraki (JP)

5,674,556 A * 10/1997 Fukumura B05C 5/0254
427/113

6,033,723 A 3/2000 Kistler et al.

2003/0140849 A1 7/2003 Kawabe

2007/0231479 A1 10/2007 Ogawa et al.

2008/0213471 A1* 9/2008 Oki et al. 427/162

2008/0261047 A1 10/2008 Shibata

(Continued)

(73) Assignee: **NITTO DENKO CORPORATION**, Ibaraki-shi (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 347 days.

FOREIGN PATENT DOCUMENTS

CN 101274315 A 10/2008

CN 101279315 A * 10/2008

(Continued)

(21) Appl. No.: **13/989,189**

(22) PCT Filed: **Nov. 24, 2011**

(86) PCT No.: **PCT/JP2011/077029**

§ 371 (c)(1),

(2), (4) Date: **May 23, 2013**

OTHER PUBLICATIONS

Japanese Office Action dated Jul. 10, 2014, issued in corresponding Japanese Patent Application No. 2010-269437, w/English translation (4 pages).

(Continued)

(87) PCT Pub. No.: **WO2012/073781**

PCT Pub. Date: **Jun. 7, 2012**

(65) **Prior Publication Data**

US 2013/0243957 A1 Sep. 19, 2013

Primary Examiner — Lisha Jiang

(74) *Attorney, Agent, or Firm* — Westerman, Hattori, Daniels & Adrian, LLP

(30) **Foreign Application Priority Data**

Dec. 2, 2010 (JP) 2010-269437

ABSTRACT

(51) **Int. Cl.**

B05C 5/02 (2006.01)

B05D 1/26 (2006.01)

B05C 3/18 (2006.01)

(57)

The invention is a method, an apparatus, and a coated product-manufacturing method each capable of applying a coating solution to a flexible backing sheet using a die coater while preventing contaminants from forming defects. A virtual line L is drawn to pass through the discharge port 74 of the die coater 7 and to extend perpendicular to the backing sheet 1, the distance D1 between a starting line P1 and a boundary line P2 is 50 mm or less, and the distance between the starting line P1 and a line on the roller P3 is 5 μm or more.

(52) **U.S. Cl.**

CPC **B05C 3/18** (2013.01); **B05C 5/0254**

(2013.01); **B05D 1/26** (2013.01); **B05D**

2252/02 (2013.01)

(58) **Field of Classification Search**

None

See application file for complete search history.

3 Claims, 4 Drawing Sheets

