



US009411199B2

(12) **United States Patent**  
**Li et al.**

(10) **Patent No.:** **US 9,411,199 B2**  
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **ARRAY SUBSTRATE AND COLOR FILTER SUBSTRATE OF DISPLAY DEVICE AND METHOD FOR MANUFACTURING THE SAME**

(71) Applicant: **BEIJING BOE OPTOELECTRONICS TECHNOLOGY CO., LTD.**, Beijing (CN)

(72) Inventors: **Cheng Li**, Beijing (CN); **Xue Dong**, Beijing (CN); **Dong Chen**, Beijing (CN); **Suzhen Mu**, Beijing (CN)

(73) Assignee: **BEIJING BOE OPTOELECTRONICS TECHNOLOGY CO., LTD.**, Beijing (CN)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 140 days.

(21) Appl. No.: **13/805,149**

(22) PCT Filed: **Sep. 29, 2012**

(86) PCT No.: **PCT/CN2012/082446**

§ 371 (c)(1),

(2) Date: **Dec. 18, 2012**

(87) PCT Pub. No.: **WO2013/060222**

PCT Pub. Date: **May 2, 2013**

(65) **Prior Publication Data**

US 2013/0105831 A1 May 2, 2013

(30) **Foreign Application Priority Data**

Oct. 24, 2011 (CN) ..... 2011 1 0327982

(51) **Int. Cl.**

**G02F 1/1343** (2006.01)

**G02F 1/1362** (2006.01)

(52) **U.S. Cl.**

CPC .... **G02F 1/134309** (2013.01); **G02F 1/136286** (2013.01); **G02F 2001/134318** (2013.01); **G02F 2001/134372** (2013.01); **G02F 2201/40** (2013.01)

(58) **Field of Classification Search**

CPC ..... **G02F 2001/134372**; **G02F 1/134309**; **G02F 1/136286**

USPC ..... **349/141**  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,259,493 B1 7/2001 Nakamura et al.  
6,449,026 B1 \* 9/2002 Min et al. .... 349/141

(Continued)

FOREIGN PATENT DOCUMENTS

CN 101078841 A 11/2007  
CN 101174638 A 5/2008

(Continued)

OTHER PUBLICATIONS

International Search Report: dated Oct. 24, 2011; PCT/CN2012/082446.

(Continued)

*Primary Examiner* — James Dudek

(74) *Attorney, Agent, or Firm* — Ladas & Parry LLP

(57)

**ABSTRACT**

Embodiments of the present invention disclose an array substrate of display device and a method for manufacturing the same, which can effectively restrain the interference by the signals over data lines with the modulation conducted by liquid crystal thereon, and improve light transmittance. The array substrate comprises: a pixel region defined by a gate line intersecting a data line. A thin film transistor, a pixel electrode, and a common electrode, which cooperates with the pixel electrode to form a multi-dimension electric field, are disposed in the pixel region. The pixel electrode is a slit-shaped electrode, and the common electrode is a plate-shaped electrode; or the pixel electrode is a plate-shaped electrode, and the common electrode is a slit-shaped electrode. An end of the plate-shaped electrode covers the data line, and a second insulating layer is disposed between a layer of the plate-shaped electrode and a layer of the data line.

**3 Claims, 2 Drawing Sheets**

