



(12) **United States Patent**
Rosenberg et al.

(10) **Patent No.:** **US 7,592,999 B2**
(45) **Date of Patent:** **Sep. 22, 2009**

(54) **HAPTIC FEEDBACK FOR TOUCHPADS AND OTHER TOUCH CONTROLS**

(75) Inventors: **Louis B. Rosenberg**, San Jose, CA (US); **James R. Riegel**, Santa Clara, CA (US)

(73) Assignee: **Immersion Corporation**, San Jose, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 82 days.

(21) Appl. No.: **11/405,811**

(22) Filed: **Apr. 17, 2006**

(65) **Prior Publication Data**

US 2006/0187215 A1 Aug. 24, 2006

Related U.S. Application Data

(63) Continuation of application No. 10/213,940, filed on Aug. 6, 2002, now Pat. No. 7,148,875, which is a continuation-in-part of application No. 09/487,737, filed on Jan. 19, 2000, now Pat. No. 6,429,846, which is a continuation-in-part of application No. 09/467,309, filed on Dec. 17, 1999, now Pat. No. 6,563,487, and a continuation-in-part of application No. 09/253,132, filed on Feb. 18, 1999, now Pat. No. 6,243,078, which is a continuation-in-part of application No. 09/156,802, filed on Sep. 17, 1998, now Pat. No. 6,184,868, and a continuation-in-part of application No. 09/103,281, filed on Jun. 23, 1998, now Pat. No. 6,088,019.

(51) **Int. Cl.**
G09G 5/00 (2006.01)

(52) **U.S. Cl.** **345/156**

(58) **Field of Classification Search** **345/156, 345/173, 184; 715/101-102, 702, 764; 463/38, 463/37; 178/18.01; 340/407.1, 825.25; 434/114**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,023,290 A 5/1977 Josephson
(Continued)

FOREIGN PATENT DOCUMENTS

EP 0556999 B1 5/1998
(Continued)

OTHER PUBLICATIONS

Bliss, James C., "Optical-to-tactile Image Conversion for the Blind," IEEE Transactions on Man-Machine Systems, vol. MMS-11, No. 1, 1970, pp. 58-65.

(Continued)

Primary Examiner—Abbas I Abdulselam

(74) *Attorney, Agent, or Firm*—Womble Carlyle Sandridge & Rice, PLLC

(57) **ABSTRACT**

A haptic feedback planar touch control used to provide input to a computer. A touch input device includes a planar touch surface that inputs a position signal to a processor of the computer based on a location of user contact on the touch surface. The computer can position a cursor in a displayed graphical environment based at least in part on the position signal, or perform a different function. At least one actuator is also coupled to the touch input device and outputs a force to provide a haptic sensation to the user contacting the touch surface. The touch input device can be a touchpad separate from the computer's display screen, or can be a touch screen. Output haptic sensations on the touch input device can include pulses, vibrations, and spatial textures. The touch input device can include multiple different regions to control different computer functions.

17 Claims, 5 Drawing Sheets

