

15

areas or types of areas based on types of functions associated with those areas, as desired. Different haptic sensations can be designed in a tool such as Immersion Studio™ available from Immersion Corp. of San Jose, Calif.

It should be noted that the regions **62** and **64** need not be physical regions of the touchpad **16**. That is, the entire touchpad **16** surface need merely provide coordinates of user contact to the processor of the computer and software on the computer can designate where different regions are located. The computer can interpret the coordinates and, based on the location of the user contact, can interpret the touchpad input signal as a cursor control signal or a different type of signal, such as rate control, button function, etc. The local touchpad microprocessor, if present, may alternatively interpret the function associated with the user contact location and report appropriate signal or data to the host processor (such as position coordinates or a button signal), thus keeping the host processor ignorant of the lower level processing. In other embodiments, the touchpad **16** can be physically designed to output different signals to the computer based on different regions marked on the touchpad surface that are contacted by the user; e.g. each region can be sensed by a different sensor or sensor array.

FIGS. **8a** and **8b** are top plan and side cross-sectional views, respectively, of another computer device embodiment **80** including a form of the haptic touchpad **16** of the present invention. Device **80** is in the form of a portable computer device such as “personal digital assistant” (PDA), a “pen-based” computer, “electronic book”, or similar device (collectively known as a “personal digital assistant” or PDA herein). Those devices which allow a user to input information by touching a display screen or readout in some fashion are primarily relevant to this embodiment of the present invention. Such devices can include the Palm Pilot from 3Com Corp., the Newton from Apple Computer, pocket-sized computer devices from Casio, Hewlett-Packard, or other manufacturers, cellular phones or pagers having touch screens, etc.

In one embodiment of a device **80**, a display screen **82** typically covers a large portion of the surface of the computer device **80**. Screen **82** is preferably a flat-panel display as is well known to those skilled in the art and can display text, images, animations, etc.; in some embodiments screen **80** is as functional as any personal computer screen. Display screen **82** is preferably a “touch screen” that includes sensors which allow the user to input information to the computer device **80** by physically contacting the screen **80** (i.e. it is another form of planar “touch device” similar to the touchpad **16**). For example, a transparent sensor film can be overlaid on the screen **80**, where the film can detect pressure from an object contacting the film. The sensor devices for implementing touch screens are well known to those skilled in the art.

The user can select graphically-displayed buttons or other graphical objects by pressing a finger or a stylus to the screen **82** at the exact location where the graphical object is displayed. Furthermore, some embodiments allow the user to “draw” or “write” on the screen by displaying graphical “ink” images **85** at locations where the user has pressed a tip of a stylus, finger, or other object. Handwritten characters can be recognized by software running on the device microprocessor as commands, data, or other input. In other embodiments, the user can provide input additionally or alternatively through voice recognition, where a microphone on the device inputs the user’s voice which is translated to appropriate commands or data by software running on the device. Physical buttons **84** can also be included in the housing of the device **80** to provide particular commands to the device **80** when the buttons are

16

pressed. Many PDA’s are characterized by the lack of a standard keyboard for character input from the user; rather, an alternative input mode is used, such as using a stylus to draw characters on the screen, voice recognition, etc. However, some PDA’s also include a fully-functional keyboard as well as a touch screen, where the keyboard is typically much smaller than a standard-sized keyboard. In yet other embodiments, standard-size laptop computers with standard keyboards may include flat-panel touch-input display screens, and such screens (similar to screen **12** of FIG. **1**) can be provided with haptic feedback according to the present invention.

In the present invention, the touch screen **82** provides haptic feedback to the user similarly to the touchpad **16** described in previous embodiments. One or more actuators **86** can be coupled to the underside of the touch screen **82** to provide haptic feedback such as pulses, vibrations, and textures; for example, an actuator **86** can be positioned near each corner of the screen **82**, as shown in FIG. **8a**. Other configurations of actuators can also be used. The user can experience the haptic feedback through a finger or a held object such as a stylus **87** that is contacting the screen **82**.

As shown in FIG. **8b**, the touch screen **82** is preferably coupled to the housing **88** of the device **80** by one or more spring or compliant elements **90**, such as helical springs, leaf springs, flexures, or compliant material (foam, rubber, etc.) The compliant element allows the touch screen **82** to move approximately along the z-axis, thereby providing haptic feedback similarly to the touchpad embodiments described above. Actuators **86** can be piezo-electric actuators, voice coil actuators, or any of the other types of actuators described above for the touchpad embodiments. As shown in FIG. **8b**, the actuators **86** are directly coupled to the touch screen **82** similarly to the touchpad embodiment of FIG. **3**; alternatively, an inertial mass can be moved to provide inertial feedback in the z-axis of the touch screen, similarly to the touchpad embodiment of FIG. **6**. Other features described above for the touchpad are equally applicable to the touch screen embodiment **80**.

In the embodiments of touch input devices (touchpad and touch screen) described herein, it is also advantageous that contact of the user is detected by the touch input device. Since haptic feedback need only be output when the user is contacting the touch device, this detection allows haptic feedback to be stopped (actuators “turned off”) when no objects are contacting the touch input device. This feature can conserve battery power for portable devices. If a local touch device microprocessor (or similar circuitry) is being used in the computer, such a microprocessor can turn off actuator output when no user contact is sensed, thus alleviating the host processor of additional computational burden.

While this invention has been described in terms of several preferred embodiments, it is contemplated that alterations, permutations, and equivalents thereof will become apparent to those skilled in the art upon a reading of the specification and study of the drawings. For example, many different types of actuators can be used to output tactile sensations to the user. Furthermore, many of the features described in one embodiment can be used interchangeably with other embodiments. Furthermore, certain terminology has been used for the purposes of descriptive clarity, and not to limit the present invention.

What is claimed is:

1. A haptic feedback device, comprising:
  - a touch screen operative to display a graphical image and to output a position signal indicative of a selected location on the touch screen in two dimensions; and