US010344504B2

(12) **United States Patent**
Dhadda et al.

(10) **Patent No.: US 10,344,504 B2**
(45) **Date of Patent: Jul. 9, 2019**

(54) **LUG NUT LOCKING SYSTEMS**

(71) Applicants: **Bhupinder Dhadda**, Puyallup, WA (US); **Ickdeep Singh**, Puyallup, WA (US)

(72) Inventors: **Bhupinder Dhadda**, Puyallup, WA (US); **Ickdeep Singh**, Puyallup, WA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 311 days.

(21) Appl. No.: **15/284,130**

(22) Filed: **Oct. 3, 2016**

(65) **Prior Publication Data**

US 2018/0094458 A1 Apr. 5, 2018

(51) **Int. Cl.**

E05B 77/44	(2014.01)
B60R 25/00	(2013.01)
B60B 7/16	(2006.01)
E05B 73/00	(2006.01)
E05B 79/02	(2014.01)
B60B 27/06	(2006.01)

(52) **U.S. Cl.**

CPC ***E05B 77/44*** (2013.01); ***B60B 7/16*** (2013.01); ***B60R 25/00*** (2013.01); ***E05B 73/00*** (2013.01); ***E05B 79/02*** (2013.01); *B60B 27/065* (2013.01); *B60B 2320/52* (2013.01); *B60B 2900/3318* (2013.01)

(58) **Field of Classification Search**

CPC E05B 77/00; E05B 77/44; E05B 79/02; E05B 83/00; E05B 85/00; B60R 25/00; B60R 25/08; B60R 25/09

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,568,370	A *	9/1951	Scuderi	B60B 3/18 301/35.52
3,135,558	A *	6/1964	Johnston, Jr.	B60B 3/16 206/335
4,161,869	A *	7/1979	Dixon	B60B 7/068 301/37.21
6,419,326	B1 *	7/2002	Rains	B60B 7/16 301/37.21
8,708,627	B2 *	4/2014	Davies	F16B 39/101 411/102
8,733,140	B2 *	5/2014	Jones	B60B 7/16 188/32
8,739,585	B2 *	6/2014	Sims	B60B 3/165 301/37.21
8,943,865	B1 *	2/2015	Bullock	B60B 7/16 292/177
9,120,446	B2 *	9/2015	Thomas	B60R 25/00
9,689,180	B2 *	6/2017	Ivarsson	B60B 3/165
2008/0127691	A1 *	6/2008	Castillo	B60B 7/16 70/225

(Continued)

Primary Examiner — Christopher J Boswell

(74) *Attorney, Agent, or Firm* — Mohr Intellectual Property Law Solutions, PC

(57) **ABSTRACT**

Lug nut locking systems, including s for securing lug nuts on a wheel of a motor vehicle comprising a frame with ratcheting apertures. In some embodiments, the device has a pair of supports that fit over the wheel's lug bolts and underneath the frame. In other embodiments, the device comprises uniquely configured securing caps that fit over the lug bolts. In still other embodiments, the device comprises a plurality of protective covers that fit over the securing caps.

19 Claims, 7 Drawing Sheets