

[54] **BALLOT FOR USE IN AUTOMATIC  
TALLYING APPARATUS AND METHOD  
FOR PRODUCING BALLOT**[75] Inventor: **James O. Narey**, Westminster, Calif.[73] Assignee: **Business Records Corporation**, Santa Ana, Calif.[21] Appl. No.: **22,396**[22] Filed: **Mar. 6, 1987**[51] Int. Cl.<sup>4</sup> ..... **B42D 15/00**[52] U.S. Cl. .... **283/5**[58] Field of Search ..... **283/5, 48 R, 75, 106,  
283/113; 250/566, 569; 346/139 R**[56] **References Cited****U.S. PATENT DOCUMENTS**

1,404,611	1/1922	Hoag	283/5
1,410,984	3/1922	Baker	
2,190,019	2/1940	Foster	283/5
3,158,316	11/1964	Clark	283/5
3,294,424	12/1966	Mathews	434/306
3,708,656	2/1973	Fielder	283/5
3,870,865	3/1975	Schneiderhan	250/566
3,891,829	6/1975	Dobras	250/566
3,892,949	7/1975	Dodson	250/566
4,074,114	2/1978	Dobras	250/566
4,431,924	2/1984	Souvamiemi et al.	250/566
4,641,240	2/1987	Boraum	434/306

Primary Examiner—Paul A. Bell

8 Claims, 3 Drawing Sheets

Attorney, Agent, or Firm—Balogh, Osann, Kramer,  
Dvorak, Genova & Traub[57] **ABSTRACT**

A ballot for use with a scanning device which reads the ballot and feeds it to a tallying or accumulating machine, the ballot being in the form of a base sheet possessing sufficient substance to facilitate the feeding of the ballot into the scanning device. The base sheet contains one or more columns of offices and the names of candidates who vie for the particular offices. Each margin of the ballot contains one or more index marks for correctly identifying the ballot orientation in the scanning device. One margin of the ballot also contains printed code marks by which the ballot style or configuration may be identified. Adjacent to each column of offices/candidates, are printed two columns of horizontally spaced timing marks, the timing marks being arranged on the lines bearing the candidate's names. A particular candidate is selected by introducing a mark between the horizontally spaced timing marks adjoining the particularly selected candidate. To visibly enhance markings between the two timing marks, the timing mark adjacent the candidate's name is in the form of an arrow head, and the other spaced timing mark is in the form of an arrow tail, so that a vote is cast when the arrow tail is connected by a line to the arrow head to thereby define a completed arrow.

