US007333822B2

(12) **United States Patent**
Laumen et al.

(10) **Patent No.: US 7,333,822 B2**
(45) **Date of Patent: Feb. 19, 2008**

(54) **METHOD FOR TRANSMITTING MESSAGES IN A TELECOMMUNICATION NETWORK**

(75) Inventors: **Josef Laumen**, Hildesheim (DE); **Joerg Reinecke**, Sickte (DE); **Frank Schange**, Hildesheim (DE); **Gunnar Schmidt**, Wolfenbuettel (DE)

(73) Assignee: **IPCOM GmbH & Co., KG**, Pullach (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 253 days.

(21) Appl. No.: **10/182,687**

(22) PCT Filed: **Jan. 25, 2001**

(86) PCT No.: **PCT/DE01/00285**

§ 371 (c)(1),
(2), (4) Date: **Oct. 29, 2002**

(87) PCT Pub. No.: **WO01/58183**

PCT Pub. Date: **Aug. 9, 2001**

(65) **Prior Publication Data**

US 2003/0109269 A1 Jun. 12, 2003

(30) **Foreign Application Priority Data**

Feb. 2, 2000 (DE) 100 04 260

(51) **Int. Cl.**
H04Q 7/20 (2006.01)

(52) **U.S. Cl.** **455/466**; 455/426.1; 455/412.1; 455/415; 455/552.1; 370/352; 370/469; 710/117

(58) **Field of Classification Search** 455/426.1, 455/412.1, 415, 466, 552.1; 370/352, 469; 710/117

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,625,670	A *	4/1997	Campana et al.	455/412.1
5,742,668	A *	4/1998	Pepe et al.	455/415
5,905,879	A *	5/1999	Lambrecht	710/117
6,038,296	A *	3/2000	Brunson et al.	379/100.11
6,195,345	B1 *	2/2001	Kramer	370/352
6,205,330	B1 *	3/2001	Winbladh	455/426.1
6,556,586	B1 *	4/2003	Sipila	370/469

FOREIGN PATENT DOCUMENTS

EP	1 091 601	4/2001
JP	11187155	7/1999
JP	11511608 T	10/1999
JP	1111511608 T *	10/1999
WO	WO 97 08906	3/1997
WO	WO 99/52247	10/1999
WO	WO 01 13656	2/2001

* cited by examiner

Primary Examiner—Steve M. D'Agosta
(74) *Attorney, Agent, or Firm*—Kenyon & Kenyon LLP

(57) **ABSTRACT**

A method is provided for transmitting messages, for example, in a telecommunications network, in which a first message service and a second message service are available. Dedicated messages of the first message service are sent using messages of the second message service. An exemplary method may permit an optimized transmission scheme to be maintained for the dedicated messages of the first message service.

26 Claims, 4 Drawing Sheets