US010061977B1

(12) **United States Patent**
Chang

(10) **Patent No.: US 10,061,977 B1**
(45) **Date of Patent: Aug. 28, 2018**

(54) **DETERMINING A MOOD FOR A GROUP**

(71) Applicant: **Snap Inc.**, Venice, CA (US)

(72) Inventor: **Sheldon Chang**, Venice, CA (US)

(73) Assignee: **Snap Inc.**, Venice, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 184 days.

(21) Appl. No.: **14/691,313**

(22) Filed: **Apr. 20, 2015**

(51) **Int. Cl.**
G06K 9/62 (2006.01)
G06K 9/00 (2006.01)

(52) **U.S. Cl.**
CPC ***G06K 9/00315*** (2013.01); ***G06K 9/00335*** (2013.01); *G06F 2203/011* (2013.01)

(58) **Field of Classification Search**
CPC G06K 9/00315; G06K 9/00335; G06F 2203/011
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,038,295	A	3/2000	Mattes	
6,980,909	B2	12/2005	Root et al.	
7,173,651	B1	2/2007	Knowles	
7,411,493	B2	8/2008	Smith	
7,535,890	B2	5/2009	Rojas	
8,131,597	B2	3/2012	Hudetz	
8,199,747	B2	6/2012	Rojas	
8,332,475	B2	12/2012	Rosen et al.	
8,363,063	B2 *	1/2013	Ou	B44D 3/003 345/589
8,718,333	B2	5/2014	Wolf et al.	
8,724,622	B2	5/2014	Rojas	
8,874,677	B2	10/2014	Rosen et al.	
8,909,679	B2	12/2014	Root et al.	
8,995,433	B2	3/2015	Rojas	
9,040,574	B2	5/2015	Wang et al.	
9,055,416	B2	6/2015	Rosen et al.	
9,100,806	B2	8/2015	Rosen et al.	
9,100,807	B2	8/2015	Rosen et al.	
9,191,776	B2	11/2015	Root et al.	
9,204,252	B2	12/2015	Root	
9,443,227	B2	9/2016	Evans et al.	
9,489,661	B2	11/2016	Evans et al.	
9,491,134	B2	11/2016	Rosen et al.	
2004/0022432	A1 *	2/2004	Hayata	G06K 9/00221 382/159

(Continued)

FOREIGN PATENT DOCUMENTS

CA	2887596	A1	7/2015

OTHER PUBLICATIONS

Leyden, John. "This SMS will self-destruct in 40 seconds", [Online]. Retrieved from the Internet: <URL: http://www.theregister.co.uk/2005/12/12/stealthtext/, (Dec. 12, 2005), 1 pg.

Primary Examiner — Samir Ahmed
(74) *Attorney, Agent, or Firm* — Schwegman Lundberg & Woessner, P.A.

(57) **ABSTRACT**

A system and method for determining a mood for a crowd is disclosed. In example embodiments, a method includes identifying an event that includes two or more attendees, receiving at least one indicator representing emotions of attendees, determining a numerical value for each of the indicators, and aggregating the numerical values to determine an aggregate mood of the attendees of the event.

15 Claims, 18 Drawing Sheets