



US010364881B2

(12) **United States Patent**
Pikovsky et al.

(10) **Patent No.:** **US 10,364,881 B2**
(45) **Date of Patent:** **Jul. 30, 2019**

(54) **TURBINE ENGINE MODULE COMPRISING A CASING AROUND A DEVICE WITH A COVER FOR RECOVERING LUBRICATING OIL**

(58) **Field of Classification Search**
CPC F02C 7/36; F02C 7/06; F05D 2260/40311;
F01D 25/18; F02K 3/06
(Continued)

(71) Applicant: **SAFRAN AIRCRAFT ENGINES**,
Paris (FR)

(56) **References Cited**

(72) Inventors: **Catherine Pikovsky**, Moissy-Cramayel
(FR); **Benoit Guillaume Farvacque**,
Moissy-Cramayel (FR)

U.S. PATENT DOCUMENTS

3,776,067 A * 12/1973 DeBruyne F16H 1/2818
184/6.12
4,271,928 A * 6/1981 Northern B64C 27/12
184/6.11

(73) Assignee: **SAFRAN AIRCRAFT ENGINES**,
Paris (FR)

(Continued)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 444 days.

FOREIGN PATENT DOCUMENTS

FR 2955085 A1 1/2010

(21) Appl. No.: **15/306,969**

OTHER PUBLICATIONS

(22) PCT Filed: **Apr. 29, 2015**

"Written Opinion," PCT Application No. PCT/FR2015/051162 (dated
Nov. 10, 2016).

(86) PCT No.: **PCT/FR2015/051162**

(Continued)

§ 371 (c)(1),

(2) Date: **Oct. 26, 2016**

Primary Examiner — Henry Y Liu

(87) PCT Pub. No.: **WO2015/166189**

(74) *Attorney, Agent, or Firm* — Womble Bond Dickinson
(US) LLP

PCT Pub. Date: **Nov. 5, 2015**

(65) **Prior Publication Data**

US 2017/0051823 A1 Feb. 23, 2017

(30) **Foreign Application Priority Data**

Apr. 30, 2014 (FR) 14 53919

(51) **Int. Cl.**

F02C 7/06 (2006.01)

F01D 25/18 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **F16H 57/0486** (2013.01); **F01D 25/18**
(2013.01); **F02C 7/06** (2013.01);

(Continued)

(57) **ABSTRACT**

The invention relates to a turbine engine module comprising a rotating device (1) having a cover (5), said cover (5) comprising radial through ports (8) for the passage of the oil escaping by centrifugation and means (10) for guiding the oil leaving said ports (8) radially outwards, and a casing (2) defining at least one portion of a lubrication enclosure of said device (1), said casing (2) comprising at least one gutter (13), arranged to recover the oil, characterized in that the gutter (13) comprises an annular bottom wall (12) having at least one discharge port, and in that the casing (2) comprises at least one other port located on the outside of the gutter (13), said at least one other port and said at least one discharge port being connected to common discharge means.

6 Claims, 2 Drawing Sheets

